

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1170'S, 1450'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF 078200B
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Riddle B
9. WELL NO.
2A
10. FIELD OR WILDCAT NAME
Blanco M.V.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T-30-N, R-10-W
N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6208' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-14-79: TD 3155'. Ran 77 jts. 7", 20#, K-55 intermediate casing, 3143' set at 3155'. Cemented w/377 cu. ft. cement. WOC 12 hrs.; held 1200#/30 minutes. Top of cement 1900'.

2-17-79: TD 5538'. Ran 80 jts. 4 1/2", 10.5#, KS casing liner, 2557' set 2981-5538'. Float collar set 5521'. Cemented w/442 cu. ft. cement. WOC 18 hrs.

3-15-79: PBTD 5521'. Tested casing to 3500#, OK. Perfed 5050, 5078, 5098, 5104, 5110, 5116, 5139, 5146, 5154, 5163, 5171, 5177, 5205, 5236, 5312, 5350, 5356, 5376, 5412, 5433, 5439, 5445, 5504' w/1 SPZ. Fraced w/68,000# 20/40 sand and 136,000 gal. water. Flushed w/6930 gal. water. Perfed 4422, 4431, 4435, 4439, 4443, 4447, 4476, 4480, 4496, 4503, 4533, 4537, 4558, 4564, 4577, 4582, 4710, 4715, 4783, 4910, 4914' w/1 SPZ. Fraced w/52,000# 20/40 sand and 104,000 gal. water. Flushed w/6552 gal. water. Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED D. G. Busco TITLE Drilling Clerk DATE March 19, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NYMOCC

