

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. SF-078511
2. NAME OF OPERATOR Union Texas Petroleum	6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A
3. ADDRESS OF OPERATOR 375 U.S. Highway 64, Farmington, New Mexico 87401	7. UNIT AGREEMENT NAME N/A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1450' FSL & 900' FEL	8. FARM OR LEASE NAME QUINN
14. PERMIT NO.	9. WELL NO. 10
15. ELEVATIONS (Show whether OF, ST, GR, etc.) 6468' G.L.	10. FIELD AND POOL, OR WILDCAT Wildcat Fruitland
	11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA Section 19-T31N-R8W
	12. COUNTY OR PARISH San Juan
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ Production casing

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drill 8-3/4" hole to 3380'.
2. Run 7", 23#, K-55 intermediate casing to 3380'.
3. Cement with 225 sx (646 cu.ft.) 65/35 POZ with 12% gel and 12-1/4# gilsonite, tailed by 200 sx (236 cu.ft.) C1 "B" containing 2% CaCl2. Circulate 11 bbls (62 cu.ft.) of cement to surface.
4. Rig down, move off.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert C. Frank

TITLE Permit Coordinator

DATE 11/17/1987

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side