

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

RECEIVED
BLM

98 JUN 22 11:44 AM '98
Lease Designation and Serial No.
NM - 25857

070 FARMINGTON, NM
If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Richardson Operating Company

3. Address and Telephone No. C/O Walsh Engineering & Production Corp.
7415 East Main Farmington, NM 87402 505-327-4892

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
885' FSL & 956 FWL, Section 21, T30N, R14W

7. If Unit or CA, Agreement Designation

8. Well Name and No.
WF Federal #21-1R

9. API Well No.
30-045-28897 30031

10. Field and Pool, or Exploratory Area
Twin Mounds FTS-PC &
Basin Fruitland Coal

11. County or Parish, State
San Juan County, NM

CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☒ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/4/98 Spud 8-3/4" surface hole. Drill to 130'. Ran 3 jts. of 7", 20#, casing and set at 128' GL. Cemented with 50 sx (59 cu.ft.) of CI "G" cement with 2% CaCl₂. Circulated 4.0 bbls of cement to surface. WOC. Nipple up BOP and pressure test to 1500# - held OK.

6/7/98 TD 6-1/4" hole at 1250' GL. Halliburton ran IES/GR and CDL logs. Ran 30 jts. of 4-1/2", 10.5#, casing and set at 1250' GL. PBTD = 1208' GL. Cemented with 70 sx (144 cu.ft.) of CI "B" with 2% metasilicate and 50 sx (59 cu.ft.) of CI "B" with 1/4#/sk celloflake. Circulated 2 bbls of cement to surface. Nipple down BOP and install wellhead. Wait on completion

RECEIVED
JUL 2 9 1998

14. I hereby certify that the foregoing is true and correct

Signed Paul C. Thomas Title Agent Date June 10, 1998

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

FARMINGTON FIELD OFFICE
BY 6-26