Submit 3 Copies to Appropriate
District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District, II
811 South First, Artesia, NM 87210

District III

## State of New Mexico Energy, Minerals and Natural Resources

## OIL CONSERVATION DIVISION

2040 South Pacheco

1000 Rio Brazos Rd., Aztec, NM 87410		2040 South Pacheco			
District IV	Santa Fe, NM <u>87505</u>				
2040 South Pacheco, Santa Fe, NM 87505			WELL API NO	).	
			(3)	30-045-30077	
		COT 2000	5 Indicate Ty	pe of Lease	
		To she she	STATE [	X FEE	
		C: TOTAL	6. State Oil &	Gas Lease No.	
		Ter 3	A 12	47, B11571-54, E3149	
SUNDRY	NOTICES AND REPORTS C	ON WELLS		e or Unit Agreement Name	
(DO NOT USE THIS FORM FOR P	ROPOSALS TO DRILL OR TO DEEF	PEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE ".	APPLICATION FOR PERMIT" (FOR	M C-101) FOR SUCH			
PROPOSALS.)				WF State 16	
1. Type of Well:	TT				
Oil Well	X Gas Well	Other			
2. Name of Operator			8. Well No.		
Richardson Operating Company #019219			#4		
<ol> <li>Address of Operator</li> <li>1700 Lincoln Street, Suite 1700, Denver, CO 80203</li> </ol>			9. Pool name or Wildcat Harper Hill FR Sand PC		
4. Well Location	ante 1700, Denver, CO 80203		Пацк	a mii rk said re	
	er <u>C</u> : <u>1035</u> feet from t	he North line and 1330	feet from the	West line	
Section	16 Township	30 Range 14W	NMPM	San Juan County	
Section		w whether DR, RKB, RT, GR,			
	·	5637' GR			
	. Check Appropriate Box to In				
	INTENTION TO:		SEQUENT RE		
PERFORM REMEDIAL	PLUG AND ABANDON	I REMEDIAL WOF	₹K Į	ALTERING CASING	
WORK TEMPORARILY ABANDON	CHANGE PLANS	X COMMENCE DR	X COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
PULL OR ALTER	MULTIPLE	X CASING TEST A	ND		
CASING	COMPLETION	CEMENT JOB			
OTHER:		OTHER:			
12. Describe proposed or c	ompleted operations. (Clearly sta	te all pertinent details, and give	pertinent dates, in	cluding estimated date of	
	work). SEE RULE 1103. For Mul				
9/6/00	Spud 8 3/4" surface hole. Drill to 135'. Ran 3 jts 7" 20# surface casing to 132.60'. Pump 5 bbls water to establish circulation. Cemented with 50 sx of Class "H" with 3% CaCl2 1/4# celloflake. Circulate 5 bbls cement to surface.				
9/7/00	Test BOP to 2000#. Test casing to 1000#. Drill to 700'.				
9/8/00	Drill to 1200'.				
9/9/00	Well TD at 1410'. Ran 32 jts of 4 1/2" 10.5# casing to 1401.80'. Cemented with 100 sxs (206 cuft) Class "B". Tail with 80 sxs (94.5 cuft) Class "B" Neat. Displaced cement with 22 bbls water. Circulate 10 bbls cement to surface.				
I hereby certify that the	e information above is true and	d complete to the best of my l	cnowledge and be	elief.	
SIGNATURE	hleen Colly	TITLE Land Manager		DATE 10/5/00	
Type or print name	Cathleen Colby		Teleph	none No. 303-830-8000	
(This space for State use)				<b>A</b> 6	
APPROVED	BY CHAPLE T. PERMIN			■ OCT 10 2000	
BY		TITLE		DATE	
Conditions of approval, if an	y:				