

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NM-04444

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Northeast Hogback Unit

8. Well Name and No.
NEHU #52

9. API Well No.
30-045-30090

10. Field and Pool, or Exploratory Area
Horseshoe Gallup Unit

11. County or Parish, State
San Juan County, NM

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Central Resources, Inc. c/o Playa Minerals & Energy, Inc.

3. Address and Telephone No.
650 N. Sam Houston Pkwy. E. Suite 500 Houston, Tx. 77060 (281) 931-3800

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
990 FNL, 1880 FNL, Sec. 3, T30N, R16W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud/ Casing Notice

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

L&B Speed Drill spudded well on 1/18/00. Drilling 8-3/4" hole.

1/20/00 Set 7", 23#, J55 casing to 322.18' with 85 sacks of class B neat cement w/ 2% CaCl.
Circulated cement to surface.

1/23/00 Drilled 6-1/4" hole 1770'. Set 4-1/2" 9.5#, J-55 casing at 1766' with 90 sacks of lead class B cement containing 3% metasilicate and 1/4# cellophane flakes/ sack
100 sacks of tail class B cement containing 2% CaCl and 1/4# cellophane flakes/ sack.
Circulated cement to surface. Float collar at 1722'.

Centralizers on 1st, 3rd, 5th, 7th, 9th and 11th joints. Pressure tested to 1500#.

14. I hereby certify that the foregoing is true and correct

Signed

Mark L. Ehrman

Title Regulatory Compliance

Date

2/13/00
ACCEPTED FOR RECORD

(This space for Federal or State office use)

Approved by

Title

Date

FEB 08 2000

Conditions of approval, if any:

FARMINGTON FIELD OFFICE
BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side