



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Form Approved.

Land Office Santa Fe
Lease No. 079222
Unit San Juan 32-5

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	XX	XX	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....			SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....			SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....			SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....			SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....			SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 18, 1963, 19

San Juan 32-5 Unit

Well No. ~~120~~ 1-20 is located 2,558 ft. from ^{XXX}N line and 400 ft. from ^{XXX}E line of sec. 20

SW/4 Section 20 T-32-N R 5-W N.M.P.M.
(Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde & Basin Dakota Rio Arriba Cty. New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6,197 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Basin Dakota & Blanco Mesa Verde test. West half of Section 20 (320 acres) dedicated to the well. Application has been made to New Mexico state officials for approval of unorthodox location.

Casing program: Drill 12-1/4" hole to approximately 1,000 feet - set 8-5/8" 24# J-55 casing, and cement to surface, using approximately 600 sacks.

Then drill 7-7/8" hole with mud to total depth of approximately 8,100 feet - and set 5-1/2" or 4-1/2" casing on bottom. Mesa Verde formation will be cemented off with approximately 200 sacks, and approximately 200 sacks will be used to cement bottom of casing.

If commercial production indicated, 2-3/8" tubing will be used to produce the Dakota and 1-1/2" to produce the Mesa Verde. Productive zones will be perforated and sand water fractured.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company La Plata Gathering System, Inc.

Address P. O. Box 728

By [Signature]
C. Beeson Neal, Agent in Farmington
Title _____

September 18, 1963

LA PLATA GATHERING SYSTEM, INC.

1-20

L

20

2558

From the SOUTH

400

RIO ARRIBA

G. L. Elevation

6187.0

Mesa Verde & Dakota

San Juan 32-5 Unit

32 NORTH

5 WEST,

the WEST

320

Blanco Mesa Verde - Basin Dakota

X

Yes X

Unitized



(Entire West Half
of Section 20

included in

Santa Fe 079222

Lease)

20



Scale 4 inches equal 1 mile

La Plata Gathering System, Inc.

C. Beeson Neal, Agent in Farmington

P O Box 728

Farmington, New Mexico

This is to certify that the above plat was prepared from notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed

13 September 1963

James P. Leese
James P. Leese M. Mex. Reg. No. 1463
San Juan Engineering Company