

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | |
|--|--|--|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | | 5. LEASE DESIGNATION AND SERIAL NO. NM 29760 |
| 2. NAME OF OPERATOR NASSAU RESOURCES, INC. | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR P.O. Box 809, Farmington, N.M. 87499 | | 7. UNIT AGREEMENT NAME Carracas Unit |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1190' FNL - 1850' FEL | | 8. FARM OR LEASE NAME Carracas Unit 23 A |
| 14. PERMIT NO. | | 9. WELL NO. #2 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7412' GL | | 10. FIELD AND POOL, OR WILDCAT WC Fruitland Coal |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T32N, R5W, NM |
| | | 12. COUNTY OR PARISH Rio Arriba |
| | | 13. STATE NM |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, surface csg., test

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MI & RU Four Corners Rig #7.
Spudded 12-1/4" hole at 10:15 pm, 10/3/88.
Drilled to 370', & ran 8 jts. of 9-5/8", 36#, J-55 csg. (347.93').
Set at 369' KB.
Cemented with 190 sx Class "B" with 2% CaCl (224 cu.ft.)
Circulated 4 bbls. to surface.
Plug down at 5:15 a.m., 10/4/88.

Drilling operations suspended after setting & testing surface casing.
Rig released 10/5/88.

RECEIVED
OCT 14 1988
OIL CON. DIV
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen

TITLE Field Supt.

DATE 10/5/88

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMDOC

*See Instructions on Reverse Side