

(November 1983)
(Formerly 9-351)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on the
reverse side)

Expires August 31, 1985

LEASE DESIGNATION AND SERIAL

NM 30014

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
NASSAU RESOURCES, INC.

3. ADDRESS OF OPERATOR
P O Box 809, Farmington, N.M. 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below)
At surface
1850' FNL - 790' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
7320' GL

7. UNIT AGREEMENT NAME
Carracas Unit

8. FARM OR LEASE NAME
Carracas Unit 28 B

9. WELL NO.
#5

10. FIELD AND POOL OR WILDCAT
Basin Fruitland Coal

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA
Sec. 28, T32N, R4W, NMPM

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETION	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANT	☐
(Other)	☐		

SUBSEQUENT REPORT OF:

WATER SHUT OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other) Spud, 5-1/2" csg., cement	☒		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded at 9:30 pm, on 6/3/89.

Ran 10 jts. of 9-5/8" 36#, casing. Total of 328'.

Set at 344' KB.

Cemented as follows:

25 sx 65/35 poz w/ 6% gel, & 2% CaCl, & 1/4#/sk celloseal (50 cu.ft.)

100 sx Class "B" w/ 2% CaCl (118 cu.ft.)

Total of 168 cu.ft.

Plug down at 11:00 am on 6/4/89.

Circulated cement to surface.

Pressure tested at 600 psi for 30 minutes. Held okay.

18. I hereby certify that the foregoing is true and correct

SIGNED James S. Hazen

TITLE Field Supt.

DATE 6/7/89

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE ACCEPTED FOR REC'D

NMOC

*See Instructions on Reverse Side

JUN 13 1989

FARMINGTON RESOURCE AREA

EX/KK