UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

Lease Designation and Serial No.

NM 28812

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals			If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well Well Other 2. Name of Operator VASTAR RESOURCES, INC. 3. Address and Telephone No. 1816 E. MOJAVE ST., FARMINGTON, NM 8740		* ****	CARRACAS UNIT 8. Well Name and No. CARRACAS FR # 106 9. API Well No. 30-039-24651 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) SENE 1650' FNL & 810' FEL SEC. 23, T-32N, F 12. CHECK APPROPRIATE BOX(s) TO INDI	₹. ₹-4W	DIET. 3 CE, REPORT, OR OTHER	BASIN FRUITLAND COAL 11. County or Parish, State RIO ARRIBA, NM R DATA
TYPE OF SUBMISSION			
Notice of Intent Subsequent Report Final Abandonment Notice	Outei	on ack air sing E-PERF & RE-FRAC	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state all pertind drilled, give subsurface locations and measured and true vertical drilled). 	ent details, and give pertinent dates, in epths for all markers and zones pertine	ent to this work.)*	proposed work. If well is directionally

Vastar elected to reperforate and refrac the Fruitland Coals in the subject well in an attempt to increase gas flow rates. Reperforated Fruitland Coal fm 3643-45(2'), 3664-80 (16'), & 3704-08 (4'), Total 22' w/ 4 spf adding 88 holes w/ 0.42" diameter and treated all perfs w/ 500 gal 10 % formic acid followed w/ 84,588 gal 25# Delta frac 140 gel w/ sandwedge containing 1,700 sx 20/40 Brady sand. After cleaning out the 5 1/2" csg to 3804' (PBTD), a 1.9", 2.76#, J-55, 10RD IJ tbg assembly was run w/ 2 GLM'S, profile nipple and WL Re-entry guide. No pkr, EOT at 3611'. Flowed and cleaned well to a flowback tank and returned the well to production. Operations started on 07/07/2000 and were completed on 07/19/2000.

*See Instruction on Reverse Side