Original + 2

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

| | be used packer | orm is not to for reporting leakage tests ast New Mexico | NORTHWEST 1 | NEW MEXICO | PACKER-LEAK | AGE TEST | ALE OL | 62 82-10/01/78 | |
|-----------------------|---------------------------|---|--|-------------------------------|-------------------------------------|---------------------------------------|--------------------------------|--------------------------------|--|
| Operator | - | | | Lease _ | Carracas Unit 22 B Carracas Unit PC | | | 7 (Upper) ** 201 (Lower) | |
| Location of Well: | Unit | G Sec22 | Twp. 32N | Rge | Rge4W | | County Rio Arriba | | |
| | NAME OF RESERVOIR OR POOL | | | TYPE OF | | METHOD OF PROD. (Flow or Art. LHt) | | PROD. MEDIUM (Tbg. or Cag.) | |
| Upper Completion | Basin Fruitland Coal | | | Gas (Shut | Gas (Shut in) Flow (Sh | | t in) Casing | | |
| Lower Completion | C | Carracas-Pictured Cliffs | | Gas | Gas Flow | | | Tubing | |
| | | | PRE-FL | OW SHUT-IN F | RESSURE DAT | īA. | | | |
| Upper Completion | lion 4-23-98 | | Length of time sh | Langth of time shut-in 7 mo. | | | Stabilized? (Yes or No) Yes | | |
| Lower Completion | Hour, date 10 AM | shul-in , 11-19-99 | and the state of t | | 8i press. psig 190 | | | Stabilized? (Yes or No) Yes | |
| | | | | FLOW TEST | NO. 1 | | | | |
| Consmenced | at (hour, de | 12 Noon, | | | Zone producing | (Upper or Lower): | | | |
| TIME (hour, date) | | LAPSED TIME SINCE* | PRES Upper Completion | SURE Lower Completion | PROD. ZONE TEMP. | | REMARKS | | |
| 12 Noon 1111-30-99 | | 24 hrs. | 90 | 190 | 50° | Csg. open | Csg. opened thru sep. | | |
| 12 No ol | | 48 hrs. | 75 | 190 + | 50° | Producing | at 74 mc | f | |
| 12 Noor | | 68 hrs. | 75 | 192 + | 50° | SI at 8 AM | 1. Logge | d off. | |
| | | | | | | | - | | |
| Oil: | 0 | uring test BOPI (Total 222 MCF | D based on MCF | Bbls. ir | | motor | av | GOR | |
| | | | MID-TE | ST SHUT-IN P | RESSURE DATA | A. | | | |
| Completion | mpletien 8 AM 12-2-99 | | 6 day | Length of time shut-in 6 days | | | Stabilized? (Yes or No) Yes | | |
| Lower 11 AM 11-19-99 | | | Length of time shut-in 18 days | | s | Stabilized? (Yes or No) Yes | | | |

***THIS IS ONE WELL BORE WITH TWO NAMES, PER NMOCD REQUIREMENTS.

FLOW TEST NO. 2

| Commenced at (hour, date) ** 9AM, 12-7-99 Zone producing (Upper or Lower): | | | | | | | | |
|--|-------------------------|------------------|------------------|------------|---------|--|--|--|
| TIME | LAPSED TIME SINCE 本本 | PRESSURE | | PROD. ZONE | | | | |
| (hour, date) | | Upper Completion | Lower Completion | TEMP. | REMARKS | | | |
| 9 AM 12-8-99 | 24 hrs. | 278 | 70 | 60 | - | | | |
| 9 AM 12 -9-99 | 48 | 280 | 80 | 60 | | | | |
| 9 AM 12-10-99 | 72 | 280 | 80 | 60 | | | | |
| 9 AM 12-11-99 | 96 | 280 | 75 | 60 | | | | |
| 9 AM 12-12-99 | 120 | 282 | 75 | 60 | | | | |
| 9 AM 12-13-99 | 144 | 282 | 75 | 60 | | | | |

| - 10 add on the during test | | | | | | |
|--|--|---|--|--|--|--|
| Oil:BOPD based onB | Bbls. in | Hours Grav GOR | | | | |
| | MCFPD: Tested thru (Orifice or Meter): | | | | | |
| Remarks: Lower completion is the only zone currently | | | | | | |
| | | | | | | |
| I hereby certify that the information herein contained is true | and complete to | the best of my knowledge. | | | | |
| Approved JAN 12 2000 19 | Operator | NASSAU REPOURCES, INC | | | | |
| | Ву | MURPHY BRASUEL My Browiel | | | | |
| By ORIGINAL SIGNED BY CHARLIE T. PERION | | • | | | | |
| DEPUTY OIL & GAS INSPECTOR, DIST. #6 | Title | FIELD SUPT. | | | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distructed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Production total during total

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no lesk was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).