

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

VASTAR RESOURCES, INC.

3. Address and Telephone No.

1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

800' FNL, 540' FEL, Section 10, T32N, R5W

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 76832

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

CARRACAS 10 A #8

9. API Well No.

30-039-28420

10. Field and Pool, or Exploratory Area

BASIN FRUITLAND COAL

11. County or Parish, State

RIO ARRIBA COUNTY, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☒

Other DRILLING OPERATIONS

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-18-00 Spud 12 1/4" hole @ 23:00. TD'd surface hole at 430' on 7-18-00 @ 23:00. Ran 9 joints 8 5/8" 24# J-55 STC casing to 423' and cemented with 300 sx Class B w/ 3% CaCl2 & 1/4 #/sx Flocc. Circulated 24 bbl to surface. Installed bradenhead & BOP. Tested BOP to 250 psi low 2000 psi high. Tested casing to 500 psi. Drilled out with 7 7/8" bit.

7-27-00 TD'd 7 7/8" hole at 4283' @ 08:00. Ran 104 joints 5 1/2" 17# K-55 LTC casing to 4280' and cemented with 1200 sx 65/35 B/Poz w/ 6% gel, 5 #/sk Gilsonite & 1/4PPS Floccle followed by 100 sx 50/50 B/Poz w/ 2% gel 0.4% halad 344, 5 #/sk Gilsonite & 1/4PPS floccle. Circulated 123 bbl cement to surface. CIP 07:30 7-28-00. ND BOP, NU Wellhead, RD.

cc: BLM, Farmington (Or + 3)

N. Hall

Well File

14. I hereby certify that the foregoing is true and correct

Signed

Charles W. King

Title **Engineer 505 599 4308**

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD
Date 8-7-00

NOV 28 2000

FARMINGTON FIELD OFFICE
BY *[Signature]*

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOCD