

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 031686

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pritchard

9. WELL NO.

3-2 (OWW)

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

**Sec. 34, T-31-N, R-9-W
N.M.P.M.**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850'S, 1550'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6168' GL, 6178' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) **Squeeze** ☒

SUBSEQUENT REPORT OF:

REPAIRING WELL ☐

ALTERING CASING ☐


ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 5-2-65 set cement retainer at 4560', squeezed open hole w/200 sacks Class "A" cement w/1/4 cu. ft. fine Gilsonite/sk., followed by 150 sacks Class "A" cement w/10% sand and 2% calcium chloride, final pressure 3000#.

En 5-8-65 total depth 5350', ran 166 joints 4 1/2", 10.5#, J-55 casing (5332.25') set at 5345.25' w/20 bbls. gel water followed by 125 sacks regular cement, 4% gel, 1/4 cu. ft. fine Gilsonite/sk. Float collar at 5311'.



18. I hereby certify that the foregoing is true and correct

SIGNED **OR G NAL SIGNED E. S. OBERLY**

TITLE **Petroleum Engineer**

DATE **5-18-65**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

B. & R. SERVICE, INC.

TEMPERATURE SURVEY

COMPANY.....EL PASO NATURAL GAS COMPANY.....
WELL.....PRITCHARD 3-2.....FIELD.....
COUNTY.....SAN JUAN.....STATE.....NEW MEXICO.....
SEC.....K-34.....TWP.....31.....RGE.....9.....

APPROX. TOP CEMENT.....3510.....

Survey Begins at.....3000.....Ft. Ends at.....5325.....Ft.
Approx. Fill-Up.....Max. Temp. 171° @ 5325'
Log Measured From.....R.T.....Run No. 1

Casing Size	Casing Depth	Diam of Hole	Depth
4 1/2" from	to	7" from	to
from	to	from	to


Date of Cementing.....5-8-65.....Time.....3:00 A.M.....
Date of Survey.....5-8-65.....Time.....9:00 A.M.....

Amount of Cement.....125 SACKS.....Type.....

Amount of Admix.....

Recorded by.....WILSON.....Witness.....

REMARKS OR OTHER



TEMPERATURE IN DEGREES FAHRENHEIT

