INSTRUCTIONS

Ge[illegible] or [illegible] sub[illegible] [illegible] prior to the ti[illegible] tion and pressure tests, and directional su[illegible] [illegible] attached hereto, to the extent required by applic[illegible] Fed[illegible] [illegible] (e.g.), forma- [illegible] All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or F[illegible] for specific instructions.

Item 1[illegible]: [illegible] elevation is [illegible] ([illegible] otherwise shown) for depth measurement [illegible] producing

Items 22 [illegible] 24: If this well is completed for [illegible] from more than one interval zone (multiple completio[illegible] interval, [illegible] intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on [illegible] for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
No Samples	-0-	33	
Shale & sand	33	305	
Shale	305	435	
Sand	435	465	
Shale	465	550	
Sand	550	560	
Shale	560	611	
Sand	611	622 T.D.	

38. GEOLOGIC MARKERS

NAME	TOP MEAS. DEPTH	TOP TRUE VERT. DEPTH
Tocito	[illegible]	548.970'
Tocito S[illegible]	6[illegible]	611.934'

U.S. GOVERNMENT PRINTING OFFICE: 1953—O-933930