
Form	9-331 g
(Feb.	. 1951)



## (SUBMIT IN TRIPLICATE)

## Lease No. Unit 078463A

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NOTICE OF INTENTION TO	D DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO	CHANGE PLANS	
NOTICE OF INTENTION TO	TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO	RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
	SHOOT OR ACIDIZE	The state of the s
	PULL OR ALTER CASING	
NOTICE OF INTENTION TO	ABANDON WELL	
	(INDICATE ABOVE BY CHECK	( MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
		September 22 19
<b>Hence</b> 'ell No. <b>1-27</b>	is located 1760 ft.	from ${R \choose S}$ line and 2316 ft. from ${E \choose W}$ line of sec. 27
6E 27	31#	13H Men
(1/4 Sec. and Sec. No.	.) (Twp.)	(Range) (Meridian)
Resid Dekete		ounty or Subdivision)  (State or Territory)
	ed depths to objective sands; sh ing points, and	ETAILS OF WORK  now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemed all other important proposed work)
Spud 8-9-61. Comented w/15	ed depths to objective sands; shing points, and	now sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemed all other important proposed work)  to 185°. Ren 10 3/4" casing to 185°.  sent 27 CeClo. Plug down 8 p.m. Circulated
Spud 8-9-61. Comented w/15	od depths to objective sands; she ing points, and prilled 15 <sup>rd</sup> hole 10 cm. regular com	to less, weights, and lengths of proposed casings; indicate mudding jobs, cemed all other important proposed work)  to 185'. Ren 10 3/4" casing to 185'.  sent 27 CeCl2. Plug down 8 p.m. Circulated  281C - held CK.
Spud 8-9-61. Coment of w/15 coment. WGC.	Prilled 15 <sup>H</sup> hole 10 cm. regular com Tested to 500 P	to 185°. Ren 10 3/4" casing to 185°.  Sent 27 CaClo. Plug down 8 p.m. Circulated SIC - held CK.
Spud 8-9-61. Coment of w/15 coment. WGC.	Prilled 15 <sup>H</sup> hole to me. regular com Tested to 500 P	to 185°. Ren 10 3/4" casing to 185°.  Sent 27 CaClo. Plug down 8 p.m. Circulated SIC - held CK.
Spud 5-9-61. Coment of w/15 coment. WGC.	Drilled 15" hole  Drilled 15" hole  O at. regular com  Tested to 600 P	to 185°. Ren 10 3/4" casing to 185°.  Sent 27 CaClo. Plug down 8 p.m. Circulated SIC - held CK.