

(SUBMIT IN TRIPLICATE)

Indian Agency Navajo Tribal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____
Lease No. 14-20-403-2037

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	RECEIVED FEB 17 1959 U. S. GEOLOGICAL SURVEY FARMINGTON, NEW MEXICO
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Sandoli Proc.</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 16, 1959

Chimney Rock
Well No. 6-A is located 660 ft. from N line and 660 ft. from E line of sec. 25
NE NE/4 Sec. 25 31N 17W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Horseshoe Gallup Ext. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5767 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

2-12-59 Total Depth 1582. Clean Out Total Depth 1550'.

Sandoli fractured Lower Gallup perforated intervals 1507'-1542' (Perf. 2 in./ft.) with 24,690 gal. oil and 24,690# sand. Breakdown pressure 800#, Maximum treating pressure 1225#, average treating pressures 1150-1175-1200#. Injection Rate--65.2 bbls./min. Flush 1554 gals. oil. Dropped 23 rubber balls two times.

2-12-59 Total Depth 1582'. Temporary Bridge Plug at 1480'.

Sandoli fractured Lower Gallup perforated intervals 1400'-1427' (Perf. 2 in./ft.) with 29,526 gals. oil and 27,000# sand. Breakdown pressure 1200#, maximum treating pressure 1600#, average treating pressures 1200-1600#. Injection Rate--48.3 bbls./min. Flush 1680 gals. oil. Dropped 27 rubber balls one time.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Products Company
Address Post Office Box 1545
Farmington, New Mexico
By ORIGINAL SIGNED BY: JOSEPH E. KREGER
Title Petroleum Engineer

