

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 29 1992

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address and Telephone No.

221 Petroleum Center Bldg., Farmington, NM 87410 (505) 325-8874

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL, 660' FWL, Section 22, T31N, R14W

5. Lease Designation and Serial No.

14-20-604-83

6. If Indian, Allottee or Tribe Name

Ute Mountain Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ute Mountain Tribal #9

9. API Well No.

10. Field and Pool, or Exploratory Area

Verde Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cement plug #1 from 3075' to 2613' (calculated).

(Pumped total 55 cubic feet cement slurry -

Capacity 168' 4-1/2" liner 14.7 cubic feet slurry

Capacity 294' 5-1/2" casing 40.3 cubic feet slurry

Total feet cemented - 168' plus 294' equals 462').

Cement plug #2 from 1751' to 1580' (calculated).

Surface cement plug from 165' (5-1/2" casing and 2-3/8" EUE tubing simultaneously perforated by Basin Perforators at 165') to surface inside and outside 5-1/2" casing.

Unable to pump mud between cement plugs because production tubing stuck in hole.

Operator will cut off casing below ground level - Weld a 1/4" steel plate across 8-5/8" casing - Erect P&A marker - Clean and restore surface.

Restoration and seeding requirements will be completed when program is received from Bureau of Land Management or Ute Mountain Tribal Indian Agency.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Virgil L. Stoabs
Vice-President

Date

May 22, 1992

(This space for Federal or State office use)

Approved by

Title

ACTING AREA MANAGER

Date

JUN 2 1992

Conditions of approval, if any:

NMSD

Benson-Montin-Greer Drilling Corp.
Ute Mountain Tribal 83 No. 9
SW SW Sec. 22, T. 31 N., R. 14 W.
San Juan County, New Mexico

Conditions of Approval

1. This Subsequent Report of Abandonment (SRA) is approved for the plugging of the well bore only. Liability under the bond is retained until surface restoration is completed and approved.
2. Once surface reclamation has been completed, the operator will submit Form 3160-5 (Sundry Notice), informing the Bureau of Land Management (BLM) of this operation. This Sundry Notice or Second Subsequent Report of Abandonment (SSRA) will be an acceptance rather than an approval action. (Instruction Memorandum No. CO-87-417).
3. Form 3160-5, Sundry Notice, will be submitted when all restoration is completed. This Sundry Notice, or Final Abandonment Notice (FAN) will be submitted only when the site is ready for inspection by an official of the BLM and/or BIA.