MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool _	Basin B	shote		F	ormatio	nDaha	nta		County_	Sen J	seb		
Initial		 -	Annu	ual		Spec	ial	-,	Date of				
									We				
									Pago Hat				
									M6523				
)2+0 of			STITE		¹ 1	myng,	Sin	Type w gle-Brad	Well gin	G. or	G.O. Dual		
ALE OI	сощртес	10n;_	A-29-1	i1	Раске			Reserv	oir Temp.				
						OBSERV	ED DATA						
ested T	hrough	(Pro	<u>ver) (</u>	Choke)	(Meter)	-			Type Ta	ps			
	Flow (Prover) (Choke)							Data	Casing Data		<u> </u>		
lo. (Line)	(Ori:	fice)	Press.	Diff.			Temp.		Temp.	Dur of	atior Flov	
SI .	Size	S:	ize	psig	h _w	°F.		°F.	 	[⊃] F•	Н		
1		3/4		233		100	1972	80	2068 502	 		7 days 3 hours	
•													
•											<u> </u>		
<u>• ! </u>				ļ		Ĺ <u></u>		1		<u> </u>			
C	oeffici	ent.		Pr		FLOW CAL			Communication		Data da		
0.	(24-Hour) $\sqrt{1}$		<i></i>			Fact	tor	Factor		Factor		@ 15.025 psia	
I			√ h _w i			F ₁		Fg	Fpv				
•				245		.9813		9463	1.621	2872.2			
. 19													
·													
					PR.	ESSURE CA	ALCU ATI	ONS					
s Liquid avity of	d Hydrod	carbon	Ratio			cf/bbl.			ific Gravi				
	. Diquit			L-e ^{-s})		deg.			ific Gravi	.ty Flow _Pc_499		i	
								P _w 51		264.2			
P _w		Pt	F	0	$(F_cQ)^2$	(F	Q) ²	D 2	$P_c^2 - P_w^2$	0.	1		
Pt. ((psia)	- t	1 0	,	(1 C/4)	(1-	cQ) _e−s)	P _w 2	Pc-Pw	1	P. P.	¥.	
								264.2	4062.2		.2A7		
osolute OMPANY	Potenti	al:	- 3,	046-MG	 	MCFPD;	n75						
DRESS	MTMT E		1323	-eu- e Jetzel	map any	Buildin	s - Midi	and, Tex					
ENT and LINESSEL	_		Longi	4 Eren	or, Ope r	ates		15	def				
OMPANY_						REMA	RKS			-et	THE		
						TUITA	IIIIO			RI,	riven	\	
										JUNG	22 1961		
									; • • • • • • • • • • • • • • • • • • •	OIL CO	N. CCIE.	1	
									į	DIS	T :		

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q Tactual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 60° F.
- PcI 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.