


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R222.4  
Approval expires 12-31-55.

Indian Agency Navajo

Allottee \_\_\_\_\_

Lease No. 1-149-126-7632  
Chimney Rock

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 21, 1957


Well No. 1 is located 1800 ft. from S line and 340 ft. from E line of sec. 23  
NE 1/4 Sec. 23 11 N 17 W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wilcox San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3458 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 11-16-57. T.B. 1800'. Plug back depth 1400'. Set plug 1400-1600 with 40 lbs. reg. cement. Run 29 joints 3 1/2", 15.500, J-33 casing (1164') set at 1171' with 30 lbs. reg. cement, 30 lbs. Foamix, 4% gel. 1/4 Flovella/cask. Hold 1800' for 30 minutes. Top of cement by temperature survey at 400'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Products Company

Address P.O. Box 1565

Farmington, New Mexico

By Van Dyke

Title Petroleum Engineer

