

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

*Caribou Four Corners, Inc.*

3. ADDRESS OF OPERATOR

*59101*

*2906 1st North Ave N, Billings, Montana*

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: *890' FSL & 600' FEL*

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE

*MH-C-1420-1950*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

*Ute*

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

*Ute Mountain*

9. WELL NO.

*#2*

10. FIELD OR WILDCAT NAME

*Verde-Gallup*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

*SESE Sec. 21, T31N, R15W*

12. COUNTY OR PARISH

*San Juan*

13. STATE

*New Mexico*

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

*GL 5682*

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 18 1981

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*This well was P & A on May 12, 1981.*

*Spotted 22 sx cement plug thru tubing 2304-2040' KB*

*Shot off and recovered 971' 4 1/2" casing.*

*Spotted 20 sx cement plug 1033' to 950' KB thru tubing*

*Spotted 10 sx cement plug 59' to surface through tubing.*

*Erected dry hole marker.*

*Moved out rig.*

*The battery will be dismantled and the location restored within the next month.*

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *James W. Shuler* TITLE *Petroleum Engr.* DATE *May 15, 1981*

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

FEB 15 1984

OIL CON. DIV.  
DIST. 3