UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY	NOTICES	AND	REPORTS	ON/	WELLS
--------	---------	-----	---------	-----	-------

(Do not use this form for proposals to drift or to deepen or plag tyck to a different reservoir, Use Form 9-331–C for such preposals.)

- $_{\text{well}}^{\text{out}} \quad [X]$ other well
- 2. NAME OF OPERATOR W.M. Gallaway
- 3. ADDRESS OF OPERATOR 101-02 Petroleum Plaza Bldg. Farmington, N.M.
- 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 AT SURFACE: 1800' FNL, 880'FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE 14-20-604-1893

- 6. IF INDIAN, ALLOTTEE OR TRIBE NAME UTE MOUNTAIN TRIBAL
- 7. UNIT AGREEMENT NAME
- 8. FARM OR LEASE NAME UTE INDIAN D
- 9. WELL NO.
- 10. FIELD OR WILDCAT NAME VERDE GALLUP
- 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 23, T31N, R15W
- 12. COUNTY OR PARISH 13. STATE SAN JUAN N.M.
- 14. API NO.
- 15. ELEVATIONS (SHOW DF, KDB, AND WD) 5524

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)



AUG 19 1981 NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY DURANGO, COLO.

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - Filled hole w/gel, water, circulated w/450 tubing sub. Spotted 30 sks cement in Gallup open hole 2613'-2513' and continued 40' up inside 4½" csg.
 - 5/6/81 Tagged top of cement 2451', stretch csg, and shot 1309' Pulled csg. Spotted 35 sks cement across 4½" STUB 1259'-1359' Spotted 35 sks cement across top of Point Lockout 950'-850'
 - Spotted 20 sks cement across bottom of surface 5/29/81 Spotted 10 sks cement top of surface, erect dry hole marker. and clean location.

Subsurface Safety Walve: Manu, and Type

Set (a)

Ft.

18. I hereby certify that the foregoing is try

APPROVED BY CONDITIONS OF APPROVAL IF ANY

SIGNED

TITLE

DATE

OIL CON. COM. DIST. 3