Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. [redacted]

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 5, 19 57

Chic-Gov't. Sec. 20
Well No. 1 is located [redacted] ft. from [N] line and 1090 ft. from [E] line of sec. 20

[redacted] Sec. 20 (¼ Sec. and Sec. No.) [redacted] (Twp.) [redacted] (Range) _____ (Meridian)

La Plata (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the [redacted] above sea level is [redacted] ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 5" Liner, set @ 5111'. Top of liner @ [redacted]'. Cemented w/200 sacks cement. Reversed out 30 sac. Displaced w/[redacted], 1200#. Completed 9:00 p.m. 1/31/57. Drilled out cement. Perforated [redacted] (20 bullets) frac'd. w/[redacted] sand, [redacted] gals. water. No break down. Injected [redacted] to [redacted] at 70 BPM. Mixed 1/2# per gal. in 10 min., & balance 1# per gal. Set bridge plug @ [redacted]'. Perforated [redacted] (20 bullets) Frac'd w/[redacted] sand & [redacted] gals. water, no break down. Pump in [redacted] to [redacted]. FP [redacted]. 67 BPM - 3/4# sand per gal. 1st 10 min., balance 1½# per gal.

Top Point Lookout: [redacted]'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Ohio Oil Co.

Address P. O. Box 130

Casper, Wyoming

COPY (ORIGINAL SIGNED)
M. J. BOYCE

By _____

Title DIVISION PRODUCTION SUPERINTENDENT

U. S. GOVERNMENT PRINTING OFFICE 16—8437-6

Form 9-331a
(Feb. 1951)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. [redacted]
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 5, 19 57

Ohio-Gov't. Sec. 20

Well No. 1 is located [redacted] ft. from [N] line and [redacted] ft. from [E] line of sec. 20

[redacted] Sec. 20 (¼ Sec. and Sec. No.) [redacted] (Twp.) [redacted] (Range) _____ (Meridian)

La Plata (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the [redacted] above sea level is [redacted] ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 5" liner, set @ [redacted]'. Top of liner @ [redacted]'. Cemented w/[redacted] sacks cement. Reversed out [redacted] sax. Displaced w/[redacted] KCl, [redacted]. Completed [redacted] p.m. 1/31/57. Drilled out cement. Perforated [redacted]' ([redacted] bullets) frac'd. w/[redacted] sand, [redacted] gals. water. No break down. Injected [redacted] to [redacted] at 70 BPM. Mixed 1/2# per gal. in 10 min., & balance 1# per gal. Set bridge plug @ [redacted]'. Perforated [redacted]' ([redacted] bullets) frac'd w/[redacted] sand & [redacted] gals. water, no break down. Pump in [redacted] to [redacted]. FP [redacted]. 87 BPM - 3/4# sand per gal. 1st 10 min., balance 1½# per gal.

Top Point Lookout: [redacted]'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Ohio Oil Co.

Address P. O. Box [redacted]

Casper, Wyoming

By COPY (ORIGINAL SIGNED) M. J. BOYCE

Title DIVISION PRODUCTION SUPERINTENDENT

U. S. GOVERNMENT PRINTING OFFICE 16—8437-6