Fori (A)	n 9-8 pril 19	181 b 52)	_
	[		

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
1-149-IND-7684
Allottee
Lease No

	GEOLOGICAL SURVI	EY Lease No
SUNDRY N	OTICES AND REP	ORTS ON WEELS ED
		REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO DRILL	SUBSEQUENT	REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT	REPORT OF SHOOTING OR ACHIEVED SURVEY
NOTICE OF INTENTION TO TEST WATER S	HUT-OFF. SUBSEQUENT	REPORT OF ALTERING CASING NEW MEXICO REPORT OF REDRILLING OR REPAIR.
NOTICE OF INTENTION TO REDRILL OR R		REPORT OF ABANDONMENT
NOTICE OF INTENTION TO SHOOT OR ACI		ARY WELL HISTORY.
NOTICE OF INTENTION TO PULL OR ALTE		
NOTICE OF INTENTION TO ABANDON WEL		
(INDICATE AI	SOVE BY CHECK MARK NATURE OF REPOR	T, NOTICE, OR OTHER DATA)
		July 27 , 19 34
	J & 1 for N line ar	and 990ft. from $\mathbb{R}$ line of sec. 22
/ell No is locate	S Inte an	id
Mass E	(Twp.) (Range)	NMPM
(14 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
undesignated	See Juen	OSMEN WEN
(Field)	(County or Subdivision)	(State or Territory)
	oor above sea level is 5461	
State names of and expected depths to ob	DETAILS OF WOR	RK
Drilled 12" hole to 65 for Drilled 8" hole to 1100 for 1410 feet. top of Galling casing. Mind between pring \$1 1410 to \$2 740 to \$3 100 to the totalled dry hole mark	DETAILS OF WOR spective sands; show sizes, weights, and letter important process and set 65 ft. 9" called the sand set 65 ft. 9" called the sand set 65 ft. 7" called the sand set 65 ft. 9" called the sand set 65 ft.	regions of proposed casings; indicate mudding jobs, cemen reposed work)  asing comented with 36 am casing. Drilled 6" hele to 45. T.D. 1410. Salies 7":  RECEIVED  JUL 3 0 1959  OIL CON. COM. DIST. 3
Drilled 12" hole to 65 & Drilled 8" hole to 1100 & 1410 feet. top of Gallage asing. Adud between pring \$1 1410 to \$2 740 to \$3 100 to \$100 to	DETAILS OF WOR spective sands; show sizes, weights, and le ing points, and all other important pu set and set 55 ft. 9" ca feet. Set 1100 ft. 7" ca p 742 top of Dahota 134 hiugs. 1360	regions of proposed casings; indicate mudding jobs, cemer reposed work)  acting comented with 36 sm casing. Drilled 6" hele to 45. T.D. 1410. Solide 7".  RECEIVED  JUL 3 0 1959  OIL CON. COM.
Drilled 12" hole to 63 & Drilled 8" hole to 1100 & 1410 feet. top of Gallan casing. Adud between pring \$1 1410 to \$2 740 to \$3 100 to \$100 to	DETAILS OF WOR  spective sands; show sizes, weights, and le ing points, and all other important po  cot and set 65 ft. 9" co  foot. Set 1160 ft. 7" co  p 742 top of Dahota 134  slugs.  1360 45 52  710 15 52  00 25 62  must receive approval in writing by the G	regions of proposed casings; indicate mudding jobs, cemer reposed work)  asing comented with 36 sm  casing. Drilled 6" hele to  45. T. D. 1410. Suited 7":  FILEVED  JUL 3 0 1959  OIL CON. COM.  DIST. 3
Drilled 12" hole to 65 & Drilled 8" hole to 1100 & 1410 feet. top of Gallan casing. Mud between pring #1 1410 to #2 740 to #3 100 to hestalled dry hole mark  I understand that this plan of work mark  Company KING OIL (  SUITE 745 - PETROLL  Address	DETAILS OF WOR spective sands; show sizes, weights, and le ing points, and all other important pu est and set 55 ft. 9" ca feet. Set 1100 ft. 7" ca p 722 top of Dahota 134 hiugs. 1360 45 52 710 15 52 80 25 52 with and sign.  sust receive approval in writing by the G COMPANY EUM CLUR PLAG.	regions of proposed casings; indicate mudding jobs, cemen reposed work)  asing comented with 36 am casing. Drilled 6" hele to 45. T.D. 1410. Salies 7":  RECEIVED  JUL 3 0 1959  OIL CON. COM. DIST. 3
Drilled 12" hole to 63 & Drilled 8" hole to 1100 & 1410 feet. top of Gallan casing. Adud between pring \$1 1410 to \$2 740 to \$3 100 to \$100 to	DETAILS OF WOR spective sands; show sizes, weights, and le ing points, and all other important pu est and set 55 ft. 9" ca feet. Set 1100 ft. 7" ca p 722 top of Dahota 134 hiugs. 1360 45 52 710 15 52 80 25 52 with and sign.  sust receive approval in writing by the G COMPANY EUM CLUR PLAG.	regions of proposed casings; indicate mudding jobs, cemer reposed work)  asing comented with 36 sm  casing. Drilled 6" hele to  45. T. D. 1410. Suited 7":  FILEVED  JUL 3 0 1959  OIL CON. COM.  DIST. 3
Drilled 12" hole to 65 & Drilled 8" hole to 1100 & 1410 feet. top of Gallan casing. Mud between pring #1 1410 to #2 740 to #3 100 to hestalled dry hole mark  I understand that this plan of work mark  Company KING OIL (  SUITE 745 - PETROLL  Address	DETAILS OF WOR spective sands; show sizes, weights, and le ing points, and all other important pu est and set 55 ft. 9" ca feet. Set 1100 ft. 7" ca p 722 top of Dahota 134 hiugs. 1360 45 52 710 15 52 80 25 52 with and sign.  sust receive approval in writing by the G COMPANY EUM CLUR PLAG.	regions of proposed casings; indicate mudding jobs, cemer reposed work)  asing comented with 36 sm  casing. Drilled 6" hote to  45. T.D. 1410. Suited 7":  FILEVED  JUL 3 0 1959  OIL CON. COM.  DIST. 3