Form 9-331 a (Feb. 1951)

0			
	,		
		l	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	S	ata	Fe	
Lease No.	SP.	077	652	
Unit	E	tet.		

SUNDRY NOTICES AND REPORTS ON WELLS

		1
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		
NOTICE OF INTENTION TO TEST WATER SHUT-OF		H -
NOTICE OF INTENTION TO RE-DRILL OR REPAIR		71
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		
NOTICE OF INTENTION TO PULL OR ALTER CASH	,	-3-5-
NOTICE OF INTENTION TO ABANDON WELL	32M (1) 1	
(INDICATE ABOVE B	Y CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
	February 27	<u>ء</u>
ast.	(NI) #4F.)	
ell No. 🙎 is located 🍱	ft. from $\left\{\begin{matrix} N \\ W \end{matrix}\right\}$ line and $\left\{\begin{matrix} M \end{matrix}\right\}$ ft. from $\left\{\begin{matrix} M \end{matrix}\right\}$ line of sec. $\left\{\begin{matrix} M \end{matrix}\right\}$; - -
(½ Sec. and Sec. No.) (Ty	wp.) (Range) (Meridian)	
, ,		
(Field)	(County or Subdivision) (State or Territory)	
ate names of and expected depths to objective s ing p	DETAILS OF WORK sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work)	em
ingposell was spadded 2/24/62 isn 10 jts., 308' of 6 5/6" tated casing with 500g pres	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs. c	emi
ingposed was spudded 2/24/62 an 10 jts., 305' of 3 5/8" sted casing with 500g presertitled cament plug 2/25/62	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	eme
ingreell was spudded 2/24/69 an 10 jts., 308' of 6 5/6" ored casing with 500% prescribed cament plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	em
ell was spudded 2/24/69 an 10 jts., 308' of 6 5/6" ored casing with 500% prescribed cament plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	eme
ell was spudded 2/24/69 an 10 jts., 308' of 6 5/6" ored casing with 500% prescribed cament plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	eme
ingreell was spudded 2/24/69 an 10 jts., 308' of 6 5/6" ored casing with 500% prescribed cament plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	eme
ell was spudded 2/24/69 an 10 jts., 308' of 6 5/6" ored casing with 500% prescribed cament plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	eme
ell was spudded 2/24/60 an 10 jts., 308' of 6 5/6" ored desing with 500% present plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	em
ell was spudded 2/24/60 an 10 jts., 308' of 6 5/6" ored desing with 500% present plug 2/26/62 tested with 500% pressure for	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	ėm
ell was spudded 2/24/69 an 10 jts., 308° of 3 5/8° sted casing with 500% pressure for drop in pressure.	sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) CREING, Landed et 321 With 230 SM. Cat.	
ell was spudded 2/24/69 an 10 jts., 305° of 3 5/5° sted casing with 500% pressure for the drop in pressure.	is and si show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) Casing, landed at 321 with 230 sm. cat. Source for 30 signifies. The lander in the lander	
ell was spudded 2/24/69 an 10 jts., 308° of 3 5/8° sted desing with 500% pressure for drop in pressure.	is and si show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coints, and all other important proposed work) Coints, and all other important proposed work) Coints, landed at 321 with 230 8%. Cot.	sd.
ing policities and the specific of the specifi	ive approval in writing by the Geological Survey before operations may be commenced work. ORIGINAL SIGNED BY JOE C. SALMO	sd.
ing policy of the state of the	ive approval in writing by the Geological Survey before operations may be commenced.	od.