

(SUBMIT IN TRIPLICATE)

Indian Agency \_\_\_\_\_

UNITED STATES

Ute Mountain Tribal

DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee \_\_\_\_\_

Lease No. 14-00-604-100

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS JUN 4 1964

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	DURAN 39, CO. 10.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 2, 1964

Ute Mountain Tribal 1-13

Well No. 1 is located 660 ft. from ☒ S line and 660 ft. from ☒ W line of sec. 13

SW 1/4 of SW 1/4, Sec. 13 31N 14W NTPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Undesignated San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5036 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Attempted to run tubing to 4617' (PETD). Unable to get below 4595'. Spotted 75 sk. cement plug from 4595 to 4600'. (Liner production slots 4617-4607').
  2. Ran casing shot to 2824', shot casing free.
  3. Pulled and laid down 9-5/8" casing.
  4. Ran tubing, spotted 100 foot cement plug from 2870 to 2770'. (Top of liner 2822'.)
  5. Spotted 100 foot cement plug from 2780 to 2780'. (Across casing cut off point.)
  6. Spotted 100 foot cement plug from 1229 to 1129'. (Across top of cliffhouse formation).
  7. Spotted 50 foot cement plug from 170 to 120'. (Base of surface casing at 177'.)
  8. Removed wellhead equipment.
  9. Spotted 10 sk. cement plug at surface and installed dry hole marker. Cleared location. Subject well officially plugged and abandoned May 25, 1964.  
177' of 13-3/8", 48#, H-40 casing left in hole, 1923' of 9-5/8", 36#, J-55 casing left in hole. 1745' of 5 1/2", 14#, J-55 (Liner) casing left in hole.
- I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California

Address Drawer "S"

Monahans, Texas

By G. G. Koendg

Title Lead Engineer