(April 1952)								
				_				

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
fountain frital
Allottee
Lease No. 11. 00 159 LL

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT	
NOTICE OF INTENTION TO REDRILL OR REPA	IR WELL SUPCEMENT PERODE OF DEDUKE HIS OF THE STATE OF TH
OTICE OF INTENTION TO SHOOT OR ACIDIZ	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER C	ASING SUPPLEMENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WELL	GEOLD WEN
	SUBSEQUENT REPORT OF REDRILLING OR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY. GETT ON THE WELL HISTORY.
(INDICATE ABOVE	SUBSEQUENT REPORT OF REDRILLING OR SUPPLEMENTARY WELL HISTORY. SUPPLEMENT
	, 19.
	77
ell No is located _	ft. from line and ft. from Evz line of sec.
FA	
(No.)	(Magades) No. 2 (Manidian)
	(Market of the Control of the Contro
(Field) Sq	(County or Standivision)
	, , , , , , , , , , , , , , , , , , , ,
e elevation of the derrick 1000	above sea level is grand ft.
2000 2000 2000 2000	2349
	DETAILS OF WORK
ite names of and expected depths to objecti	· · · · · · · · · · · · · · · · · · ·
sing retery rig, set appr	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- points, and all other important proposed work) Oximately 180° of 32.75, Balls, 10-3/4° surface casing
sing retery rig, set appr 13-3/4" hele. Girculate 3/4" hele using med to to se or more cores in Galla relation to drill stem to a College is non-productive abote expected at 2500°.	oximately 120° of 32.75%, Boll, 10-3/4° surface encing points, and all other important proposed work) oximately 120° of 32.75%, Boll, 10-3/4° surface encing exceeds to surface and tast for water shut-off. Brill to top of the Gallup Sandstone expected at 1900°. Cut a section and on the besis of core information, make to If Gallup Sandstone is productive, sand oil-free. •, ream core hele to 8-3/4° and carry 8-3/4° hole to If production is found in oither the Gallup or Behate.
ring rotery rig, set appril 13-3/4" halo using med to to to or more eases in Galim scinion to drill stem test Galimp is non-productive total emported at 2500°, as easing string will be to the above somes are	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements points, and all other important proposed work) commutally 120° of 32.75%, Belle, 10-3/4° surface casing a semant to surface and tast for water simt-off. Brill to top of the Gallup Sandstone expected at 1900°. Gut a section and on the basis of core information, make to If Gallup Sandstone is productive, sand oil-free. The core hale to 8-3/4° and earry 8-3/4° hole to If production is found in either the Gallup or Babete, 166, 1-55, 7°, commuted by Halliburton and tested. If non-productive, plug and abandon.
ing retery rig, set approximately. Circulate 13-3/4" hele using mud to the or more cores in Galling is non-productively is non-productively expected at 2500°, as easing string will be the of the above somes are understand that this plan of work must re-	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements points, and all other important proposed work) oximately 120° of 32.75%, No.66, 10-3/Ar surface energy community to surface and tast for water shut-off. Brill to top of the Gallup Sandstone expected at 1900°. Gut p section and on the basis of core information, make t. If Gallup Sandstone is productive, sand oil-free, ream core help to 8-3/Ar and carry 8-3/Ar hole to If production is found in either the Gallup or Behote, 100°, 1-55, 7°, communed by Halliburton and tested.
sing retery rig, set approximately. Girculate 13-3/4" hele using much to the er more cores in Gallan sisten to drill stem to a Gallan is non-productive total expected at 2500°, as easing string will be the of the above somes are	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements points, and all other important proposed work) commutally 120° of 32.75%, Belle, 10-3/4° surface casing a semant to surface and tast for water simt-off. Brill to top of the Gallup Sandstone expected at 1900°. Gut a section and on the basis of core information, make to If Gallup Sandstone is productive, sand oil-free. The core hale to 8-3/4° and earry 8-3/4° hole to If production is found in either the Gallup or Babete, 166, 1-55, 7°, commuted by Halliburton and tested. If non-productive, plug and abandon.
ting retery rig, set appril 13-3/6" hele using mud to to or more cores in Gallin cision to drill stem test Galling is non-productive to expected at 2500°. Se easing string will be to the above somes are understand that this plan of work must re-	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements points, and all other important proposed work) commutally 120° of 32.75%, Belle, 10-3/4° surface casing a semant to surface and tast for water simt-off. Brill to top of the Gallup Sandstone expected at 1900°. Gut a section and on the basis of core information, make to If Gallup Sandstone is productive, sand oil-free. The core hale to 8-3/4° and earry 8-3/4° hole to If production is found in either the Gallup or Babete, 166, 1-55, 7°, commuted by Halliburton and tested. If non-productive, plug and abandon.
ing retery rig, set appril 13-3/4" hele using mud to to or more cores in Galling cision to drill stem test Galling is non-productive beta expected at 2500°, a casing string will be the of the above somes are understand that this plan of work must rempany—Claude N. Carrell	ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements points, and all other important proposed work) commutally 120° of 32.75%, Belle, 10-3/4° surface casing a semant to surface and tast for water simt-off. Brill to top of the Gallup Sandstone expected at 1900°. Gut a section and on the basis of core information, make to If Gallup Sandstone is productive, sand oil-free. The core hale to 8-3/4° and earry 8-3/4° hole to If production is found in either the Gallup or Babete, 166, 1-55, 7°, commuted by Halliburton and tested. If non-productive, plug and abandon.

U. S. GOVERNMENT PRINTING OFFICE 16-8437b-

C.M.Carroll Company Ute Well No. 1 Lease R. 15 W N.M.P.M. T. 31 N Sec 14

Location 615 feet from south line, 734 feet from

5676 GL. Elevation:

San	Juan	County			New Me	xico	
	1		, 1 1 4 1				
			 		ļ		
			********	********			
			SECTI	ON 14			
	 		·	••••			
	• • • • • • • • • • • • • • • • • • •					6 6 6 1	
						0	734'
	 				· ·	15	

RECEIVED

Scale-4 inches equal 1 mile.

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief

Registered Professional Engineer and Land Surveyor

SEP

OIL CON. COM

DIST. 3

Surveyed

August 17

Heal: