

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. **MM-021124**
Unit _____
Newberry Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 26, 1960

Well No. 1 is located 930 ft. from N line and 990 ft. from W line of sec. 17

SW 1/4 Sec. 17 (1/4 Sec. and Sec. No.) 31N (Twp.) 12W (Range) 100W (Meridian)

Basin Dakota (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 5943 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

12/20/60 Total Depth 7122' Plugged Back 7079'
Ran & set 218 jts. 5 1/2" 17# J-55 casing set at 7114' KB - DV tool @ 4919
w/225 ex 50/50 permix 4% gel & 100 ex neat w/50 gal. latex cement. Plug
down 8:00 AM - 2nd stage thru DV tool w/175 ex 50/50 permix 4% gel / 100
ex 50/50 permix 2% gel & 12 1/2# gilsonite per sack. Plug down 2:00 PM -
Nipped up & drilling rig released 4:00 PM.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Southwest Production Company

Address 162 Petr. Center Bldg.

Farmington, New Mexico

Original signed by
Carl W. Smith

By _____

Title Production Supt.