SOUTHERN UNION GAS COMPANY

BURT BUILDING
DALLAS 1, TEXAS

June 25, 1952



RE: Aztec Oil & Gas Company's Harper No. 1 Well

Mr. Al Greer New Mexico Oil Conservation Commission P. O. Box 697 Aztec, New Mexico

Dear Mr. Greer:

EXPLORATION DEPARTMENT

MANAGER

VAN THOMPSON

Attached are four copies of the completion log and four copies each of the Electric log and Gamma Ray log covering Aztec Oil and Gas Company's Harper No. 1 well, located 1650' North of South line and 840' West of the East line of Section 14, T-31-N, R-12-W, N.M.P.M., San Juan, New Mexico.

Yours very truly,
Van Thompson

VT/lm Attachments

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

JUN 7 1952 OIL CON. COM.

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the tork specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING	Indicate nature of report by checking below.		
OPERATIONS	REPORT ON I	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON I	PULLING OR OTHERWISE CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON I	DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			
	June 6, 1952	Fermington, New Mexico	
	Date	Place	
Following is a report on the work done and the results	obtained under the heading no	ted above at the	
Astec Oil and Cas Company	Tarper	Well Noin the	
Company or Operator 11 Of Sec.	Lease 31-N	, R. 12W , N. M. P. M.,	
Blanco-La Plata	San Juan	County.	
The dates of this work were as follows:	/20/59. 5-26-52		
Notice of intention to do the work was (was not) subr	nitted on Form C-102 on	, 19,	
Rotary tool depth 1,900, o	ement job failed. C	able tool moved on and	
recemented 5-1/2" casing at Drilled cement plug May 26, with 500% pressure, hole dr	th,900 with 200 sac , 1952, swabbed hole y.	ks, May 20, 1952. dry. Tested for 2 hours	
recemented 5-1/2" casing at Drilled cement plug May 26, with 500# pressure, hole dr	t 4,900' with 200 sac, 1952, swabbed hole	ks, May 20, 1952. dry. Tested for 2 hours	