	Fori (A	<b>m. 9-:</b> pril 19	<b>331 b</b>  52)	
			!	
	   <b></b> -			
1				

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency (160-Manufedia
Allottee
Lease No11-20-694-120

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	The state of the s
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHE	CK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
'ell No. 18 located 1816	ft. from $\begin{Bmatrix} E \\ S \end{Bmatrix}$ line and respect ft. from $\begin{Bmatrix} E \\ WV \end{Bmatrix}$ line of sec.
Ex State State (State )	
W. March	(Magnigan)
(Field)	(County or Subdivision) (State or Territory)
ne elevation of the derrick floor above	sea level is the
	ocu level is Lightman. It.
1	
	DETAILS OF WORK
ate names of and expected depths to objective sands	; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments
tate names of and expected depths to objective sands ing points,	DETAILS OF WORK  s; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- and all other important proposed work)
A bridge plag was set at 2 716-24, 2996 - 60, and 2968 - reced with 20,000 gal lease of 24,000 pei. Presently the we	is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement, and all other important proposed work)  755'. The Sir cooling was them performed from So with 2 job state our foot. The well was them rule and 20,000 send. The svg. rate was 35 FM  ANY 6 1950  OIL CON. CO. DIST. 3
A bridge plug was set at 3 716-24, 2736 - 60, and 2768 - reced with 20,000 gal lease of 24,000 pai. Presently the well with the set of the set	is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement, and all other important proposed work)  The SP cooling was them perforated from the second second and so that the second sec
A bridge plag was set at 2 916-24, 2996 - 60, and 2968 - reced with 20,000 gal lease of 1 24,000 pei. Presently the we	is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement, and all other important proposed work)  The SP cooling was them perforated from the second second and so that the second sec
A bridge plag was set at 3 716-24, 2796 - 40, and 2968 - reced with 20,000 gal lease of 24,000 pei. Presently the west must receive apompany	is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement, and all other important proposed work)  The SP cooling was them perforated from the second second and so that the second sec
A bridge plac was set at 3 Mo-Si, 2796 - 60, and 2968 - cod with 20,600 gal losses of 2,600 pai. Presently the was supported that this plan of work must receive apompany 35 Audiord Cil. Company 1581	s, show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement, and all other important proposed work)  30 with 2 jet state per foot. The well we then performed and 20,000 state. The sug, rate was 36 May 6 1957  MAY 6 1957  OIL CON. Control of the performance of the perform