

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
W.M. Gallaway
3. ADDRESS OF OPERATOR
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/25/81 Filled hole w/gel water circulated w/45⁰ tubing sub
Spotted 50 sks cement over Gallup open hole zone 1987' - 1886'
and continue up 50' into 4½" csg.

5/18/81 Tagged cement 1670', shot csg. @ 640', pulled csg.,
Spotted 18 sk cement 640' - 590' across STUB
Spotted 25 sk cement across Point Lookout 550'-450'
Spotted 18 sk cement across Bottom of Surface.

5/29/81 Spotted 10 sk cement top of hole and erect dry hole marker,
clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert A. Bush

TITLE

Agent

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY

David J. Miller

TITLE

Assistant

DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

FEB 28 1984

OIL CON. DIV.
DIST. 3