

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. MAKE DESIGNATION AND SERIAL NO.

NM-01594

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-9 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 32-9 U #13

9. API WELL NO.

30-045-10761

10. FIELD AND POOL, OR WILDCAT

Blanco PC/Blanco MV

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

G
Sec. 14, T-31-N, R-10-W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☐ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. REMVR. ☒ Other ☐

2. NAME OF OPERATOR

Burlington Resources Oil & Gas Company

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87402 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1650' FNL, 1650' FEL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED 3-7-53 16. DATE T.D. REACHED 3-27-53 17. DATE COMPL. (Ready to prod.) 10-5-96 18. ELEVATIONS (DF, RKE, RT, GR, ETC.)* 6332 GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 5555 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY* 2 23. INTERVALS DRILLED BY 0- 5555 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 3134-3158 Pictured Cliffs 25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN
CBL-CCL-GR

Commingled w/Mesaverde

27. WAS WELL CORRED

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8	25.4#	170		135 sx	
7	23#	4793		300 sx	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
5 1/2	4660	5546	200		2 3/8	5430	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

3134-3158 w/24 holes total

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3134-3158	495 bbl 30# linear gel
	100,000# 20/40 Ariz sd
	386,730 SCF N2

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
10-5-96		Flowing				SI	
DATE OF TEST	HOURS TESTED	CHOKES SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
10-5-96			→		869 Pitot Gauge		
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	RECEIVED		WATER—BBL.		OIL GRAVITY-API (CORR.)
	SI 298	→			ACCEPTED FOR RECORD		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE Regulatory Administrator

FARMINGTON DISTRICT OFFICE
OCT 29 1996

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
			Pump 500 sx Class "B" neat cmt w/0.3% fluid loss @ 3214' Pump 175 sx Class "B" neat cmt w/0.3% fluid loss @ 3214' Pump 225 sx Class "B" neat cmt w/2% calcium chloride @ 1111-1142' Pump 30 sx Class "B" cmt w/2% calcium chloride @ 1015-1165 Pump 200' cmt @ 1059-1259	Ojo Alamo Kirtland Fruitland Pict.Cliffs Lewis Cliff House Menefee Point Lookout	1530 1582 2697 3133 3340 4651 5007 5331	

38.

GEOLOGIC MARKERS