Form 3160-5 (June 1990)

UNITED STATES

FORM APPROVED

(Julie 1990)	DEPARTMENT OF BUREAU OF LANI		Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
	600-3531		
Do not use this for	SUNDRY NOTICES AND m for proposals to drill or e "APPLICATION FOR PEI	to deepen or reentry to a different reservoir.	6. Il Indian, Allottee or Tribe Name
	SUBMIT IN T	TRIPLICATE APR 2002	7. If Unit or CA, Agreement Designation
I. Type of Well Oil Well Gas Well	Other		MMYKOKS Sallu 8. Well Manse and No.
2. Name of Operator Lite	leum 100	NMOCD	9. API Well No.
3. Address and Telephone No.	a Brazos	astec n W187410	30-045-1080 7 10. Field and Pool, or Exploratory Area
	Sec., T., R., M., or Servey Description	on)	11. County or Parish, State
Unit Lette	UF 1973	FAL 1941 FWL	Sanfrian
12. CHECK A	PPROPRIATE BOX(s) TO	INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SU	JBMISSION	TYPE OF ACTION	
Notice of I		Abandonment Recompletion	Change of Plans New Construction
Subsequent	Report	Plugging Back	Non-Routine Fracturing Water Shut-Off
Final Aban	donment Notice	Casing Repair Altering Casing	Conversion to Injection
		Other	Dispose Water (Note: Report results of multiple completion on We
13. Describe Proposed or Compl	leted Operations (Clearly state all pertine	ent details, and give pertinent dates, including estimated date of start	Completion on Brownships Brown and London
give subsurface location	ns and measured and true vertical depth	hs for all markers and zones pertinent to this work.)*	and my proposed work it would be discussibly dis-
S	ee attack	ment	
Ţ.			•
			.•
		THE HOUSE TO SEE	n FOR RECOR
		E POINGTON OF LA COME	0 4 9703
			SAS OFFICE
4 I hereby period in the	AN 1	<u> </u>	
4. I hereby certify that the fore	Hechwon	_ Title V& A Supervisor	Date 8-3-1-01
(This space for Federal or S	1	Tite	Date
Conditions of approval, if a	ny:		



Key Energy Services, Inc. Four Corners Division 5651 US Highway 64 P.O. Box 900 Farmington, NM 87499

Phone: 505-327-4935 Fax: 505-327-4962

P&A OPERATION CEMENT SERVICE REPORT

WELL NAME: MANY ROCKS GALLUP UNIT #20

TOTAL PLUGS SET: 2

DATE STARTED: 08-27-01

TOTAL SACKS USED: 154 SX

DATE COMPLETED: 08-31-01

STATE WITNESS: H. VILLENUEVA

TRIBE WITNESS: N/A

MOL AND SPOT RIG AND PLUGGING EQUIPMENT. RU RIG. POH AND LD2 RODS. PARAFIN WAS HEAVY AND PUMP WAS PULLING AT 10000#. RU HOT OILER AND ATTEMPTED TO TREAT TBG BUT PRESSURED UP TO 1000 PSI. TREATED CSG WITH 30 BBL HOT WATER. WAIT 30 MINUTES. LD 17- RODS. PUMP STUCK IN TBG. RU HOT OILER AND TREATED CSG WITH 70 BBL. POH AND LD 50- 5/8" RODS AND PUMP. HOT OULED TBG WITH 30 BBL WATER. ND WELLHEAD AND NU BOP, TESTED BOP. POH AND STRAP OUT WITH 1741.95' OF 2 3/8" TBG.

PLUG #1 (GALLUP, PERFORATIONS, 1249' - 1524'), PU AND RIH WITH 4 ½" RETAINER AND SET AT 1523'. CIRCULATED CASING WITH WATER. PRESSURE TESTED CASING TO 500 PSI AND HELD GOOD FOR 15 MINUTES. STUNG INTO RETAINER AND ESTABLISHED INJECTION RATE INTO PERFORATIONS AT 1 BPM WITH 1300 PSI. PUMPED 90 BBL OF WATER AND OIL INTO FORMATION. STUNG OUT OF RETAINER AND BALANCED 22 SX CL. B CEMENT PLUG ON TOP OF RETAINER. POH.

PLUG #2 (SURFACE, 0' - 340'), RIH WITH WIRELINE AND PERFORATED SQUEEZE HOLES AT 340'. POH. ESTABLISHED CIRCULATION TO SURFACE WITH WATER OUT THE BRADON HEAD. MIXED 124 SX CL. B CEMENT TO CIRCULATE GOOD CEMENT TO SURFACE. RD RIG AND DUG CELLAR. CUT OFF WELLHEAD AND INSTALLED DRY HOLE MARKER ON 9-04-01.

NATHAN E. CRAWFORD. P&A SUPERVISOR

State of New Mexico Submit 3 Copies Form C-103 to Appropriate District Office Energy, Minerals and Natural Resources Department Revised 1-1-89 **DISTRICT I** OIL CONSERVATION DIVISION WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2009 30-045-16864 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease STATE FEE DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 SEP 2001 6. State Oil & Gas Lease No. 600-3531 SUNDRY NOTICES AND REPORTS ON WELLS DIV (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OF TO DEEPEN OF BLUG BASISTO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSTALS.) Many Locks bradling 1. Type of Well: METT GYZ. $\Gamma \lambda$ WELL 2. Name of Operator & Well Na. Petkeleum Manufocks 3. Address of Operator 9. Pool name or Wildcat 1000 fue brayes
Well Location 8.7410 1973 Feet From The NaRTh Line and 1941 Feet From The Wast San Juin Section Township **NMPM** County Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Physical & ABandoned well as per Procedures Rounded with Con Mark. See ATTacked Report For Detailed Externation I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TYPE OR PRINT NAME A THE ROLL FORD

(This space for State Use)

APPROVED BY

DATE

AA SUDERVISER

SIONATURE -



Key Energy Services, Inc.

Four Corners Division 5651 US Highway 64 P.O. Box 900 Farmington, NM 87499

Phone: 505-327-4935 Fax: 505-327-4962

P&A OPERATION CEMENT SERVICE REPORT

WELL NAME: MANY ROCKS GALLUP UNIT #20 TOTAL PLUGS SET: 2

DATE STARTED: 08-27-01 TOTAL SACKS USED: 154 SX

DATE COMPLETED: 08-31-01 STATE WITNESS: H. VILLENUEVA

TRIBE WITNESS: N/A

MOL AND SPOT RIG AND PLUGGING EQUIPMENT. RU RIG. POH AND LD2 RODS. PARAFIN WAS HEAVY AND PUMP WAS PULLING AT 10000#. RU HOT OILER AND ATTEMPTED TO TREAT TBG BUT PRESSURED UP TO 1000 PSI. TREATED CSG WITH 30 BBL HOT WATER. WAIT 30 MINUTES. LD 17- RODS. PUMP STUCK IN TBG. RU HOT OILER AND TREATED CSG WITH 70 BBL. POH AND LD 50- 5/8" RODS AND PUMP. HOT OULED TBG WITH 30 BBL WATER. ND WELLHEAD AND NU BOP, TESTED BOP. POH AND STRAP OUT WITH 1741.95' OF 2 3/8" TBG.

PLUG #1 (GALLUP, PERFORATIONS, 1249' - 1524'), PU AND RIH WITH 4 ½" RETAINER AND SET AT 1523'. CIRCULATED CASING WITH WATER. PRESSURE TESTED CASING TO 500 PSI AND HELD GOOD FOR 15 MINUTES. STUNG INTO RETAINER AND ESTABLISHED INJECTION RATE INTO PERFORATIONS AT 1 BPM WITH 1300 PSI. PUMPED 90 BBL OF WATER AND OIL INTO FORMATION. STUNG OUT OF RETAINER AND BALANCED 22 SX CL. B CEMENT PLUG ON TOP OF RETAINER. POH.

PLUG #2 (SURFACE, 0' - 340'), RIH WITH WIRELINE AND PERFORATED SQUEEZE HOLES AT 340'. POH. ESTABLISHED CIRCULATION TO SURFACE WITH WATER OUT THE BRADON HEAD. MIXED 124 SX CL. B CEMENT TO CIRCULATE GOOD CEMENT TO SURFACE. RD RIG AND DUG CELLAR. CUT OFF WELLHEAD AND INSTALLED DRY HOLE MARKER ON 9-04-01.

NATHAN E. CRAWFORD. P&A SUPERVISOR