

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
W.M. Galloway
3. ADDRESS OF OPERATOR  
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL, 640 Fe1  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

**RECEIVED**  
AUG 19 1981  
U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

5. LEASE  
14-20-151-46
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
UTE MOUNTAIN INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
UTE INDIAN A
9. WELL NO.  
3X
10. FIELD OR WILDCAT NAME  
VERDE GALLUP
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 15, T31N, R15W
12. COUNTY OR PARISH  
SAN JUAN
13. STATE  
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5677 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/27/81 Filled hole w/gel water, circulated w/45<sup>0</sup> tubing sub  
Spotted 15 sk cement across Gallup perf. 1892' to 1857' and continue up 50' into 5½" csq.

5/19/81 Stretch csg., shot @ 1300'

5/20/81 Pulled csg., tagged cement top inside csg. stub 1780'  
Spotted 15 sk. cement 1325' to 1275' across stub  
Spotted 30 sk. Cement 450' - 350' Across Point Lookout  
Spotted 20 sk. Cement bottom of surface csg.

6/6/81 Spotted 10 sk. cement in top of hole, and erect dry marker and clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Robert D. Bush* TITLE *Agent*

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

\*See Instructions on Reverse Side

