

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well ☐ other
2. NAME OF OPERATOR
W.M. Gallaway
3. ADDRESS OF OPERATOR
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL, 640 Fel
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
AUG 19 1981
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE
14-20-151-46
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE MOUNTAIN INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
UTE INDIAN A
9. WELL NO.
3X
10. FIELD OR WILDCAT NAME
VERDE GALLUP
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 15, T31N, R15W
12. COUNTY OR PARISH
SAN JUAN
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5677 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/27/81 Filled hole w/gel water, circulated w/45⁰ tubing sub
Spotted 15 sk cement across Gallup perf. 1892' to 1857' and continue
up 50' into 5½" csq.

5/19/81 Stretch csg., shot @ 1300'

5/20/81 Pulled csg., tagged cement top inside csg. stub 1780'
Spotted 15 sk. cement 1325' to 1275' across stub
Spotted 30 sk. Cement 450' - 350' Across Point Lookout
Spotted 20 sk. Cement bottom of surface csg.

6/6/81 Spotted 10 sk. cement in top of hole, and erect dry marker and
clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert D. Burk TITLE *Agent*

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY

David J. Miller

TITLE

Area Manager

DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

FEB 28 1984

OIL CON. DIV.
DIST. 3