



(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allettee 11-00-000-000

Lease No. 11-00-000-000

CORRECTED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

CORRECTED

July 1, 1963

Well No. 1 is located 999 ft. from N line and 999 ft. from E line of sec. 25
NE 1/4 Section 25 30N 10W 100W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5117.6 ft. Unadjusted Ground Level

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Rotary drilling equipment will be used to drill to approximately 7500'. A Russian tool. Casing program 6" of 13-3/8" cemented to surface. 4 1/2" of 13-3/8" cemented with required cement. If water flow above of 7" expected with 13-3/8" above then. If production is anticipated the required cement of 4 1/2" or 5" production casing will be run and cemented with sufficient volume of cement to cover the highest potentially productive zone. Approximately four drill stem tests and 150' of casing are anticipated as shown developing below 4500'. The program will consist of native sand from surface to 5000', and a low solids oil completion from 5000' to total depth. Electric logs, etc. will be run prior to setting production casing or abandonment of well. Stimulation treatments such as acidizing or fracturing may be employed in completion.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Navajo Oil & Refining Company

Address P. O. Box 3000

Flagstaff, Arizona

By COPY (ORIGINAL SIGNED) B. M. BRADLEY

Title Dist. Eng.



