(April 1952)							
	X						

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Fo Bi	orm appr idget By	reau N	o 42-R3	15Q 4
	1	te T	lount	ai.
indian A	rency			
-				
Allettee .	14-8	0-16	1-4	 }

SUNDRY	NOTICES	AND REPO	ORTS ON WELL	EIVEM			
NOTICE OF INTENTION TO DRILL		SUBSEQUENT	REPORT OF WATER SHUT-OFF	<u> </u>			
NOTICE OF INTENTION TO CHANGE	E PLANS	SUBSEQUENT REPORT OF SHOOTING OR AUTHORING 1963					
NOTICE OF INTENTION TO TEST W	ATER SHUT-OFF	SUBSEQUENT I	SUBSEQUENT REPORT OF ALTERING CASING				
NOTICE OF INTENTION TO REDRIL	L OR REPAIR WELL	SUBSEQUENT I	REPORT OF REDRILLINGSOFT PRIPA	BICAL SHOW			
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	SUBSEQUENT REPORT OF REDRILLINGSOFGET HIGHCAL SURVEY					
NOTICE OF INTENTION TO PULL O	R ALTER CASING	SUPPLEMENTARY WELL HISTORY					
NOTICE OF INTENTION TO ABANDO	ON WELL.	Boyart	of sand-oil fractur	ing I			
(INDI	CATE ABOVE BY CHECK MA	RK NATURE OF REPORT,	NOTICE, OR OTHER DATA)				
			December 26,	, 19 68			
Well No. Astee Ho. Is	ocated 585 ft.	from S line and	1 2238 ft. from \( \bigve{\mathbb{E}} \) line	e of sec			
SWE Sec. 10	81 North		W.M.P.M.				
(4 Sec. and Sec. No.) Verde Gallup	(Twp.)	(Range)	(Meridian)	-			
(Field)	(Com	nty or Subdivision)	(State or Terr	ltory)			
State names of and expected depth	s to objective sands; show ing points, and s	sizes, weights, and leng all other important pro	rths of proposed casings; indicate r posed work)	nudding jobs, cement-			
Sand oil fracts of oil and 30,0 and treated at rate (over-all) 780 barrels.	and-oil fractu red open hole 300 lb. of sise 800 to 1100 psi 34.9 barfole	re treatment from 1869' to 10-20 sand. . Flushed wi per min. Tot	was performed on De 2017' (TD) with 25 Fermation broke de th 2500 gal. ef eil al frae cil used 30 RL	25, 1962. 2,400 ml. m at 380 psi 1,10001 m 1,10001			
	Sind Place		1 - 01	7 . 1			
Phoenix,	risons		S. a. S.	nent			
		— т	Agent & Consulti	ng Geologist			