


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Navajo Tribal
Center. 14-00-401-0001
Allottee Trust #140
Lease No. Navajo #1



SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|--|-------------------------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | RECEIVED AUG 31 1960 |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
SARASOTA, NEW MEXICO

August 29

19 60

Well No. 23 is located 667 ft. from N line and 880 ft. from W line of sec. 14

14 Sec. 14
(4 Sec. and Sec. No.)

31N
(Twp.)

37W
(Range)

100W
(Meridian)

Horseshoe Gallup
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

Ord. level

The elevation of the ~~device face~~ above sea level is 5279 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spud 12:15 am, 8/26/60.

Cemented 5 jts, 105' of 8-5/8", 2 1/2" lapweld casing @ 20' w/90 am treated w/25 Gell. Circulated cement. Plug down 6:30 pm, 8/22/60. Tested 8-5/8" casing w/900 psi for 15 minutes; hold ok.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Secony Mobil Oil Company, Inc.

Address P. O. Box 3972

Durango, Colorado

By P. M. Barry

Title Dist. Prod. Supt.