Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

	I OF THE INTERIOR	Expires. March 51, 1995			
BUREAU OF I	5. Lease Designation and Serial No. 14-20 - 600 - 3531				
AUNDRY MOTICES	6. If Indian, Allottee or Tribe Name				
SUNDRY NOTICES					
Do not use this form for proposals to dri Use "APPLICATION FOR	10 ava jo 11.20				
SUBMIT	7. If Unit or CA, Agreement Designation				
1. Type of Well					
Oil Gas Well Other	8. Well Name and No.				
2. Name of Operator BK Petroleum I.	9. API Well No.				
% NMOCO					
3. Address and Telephone No.	3004510840				
1000 Rio Brazos Rd. Azrec	NM 87410 334-6178	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey D	Many Rocks Gallup 11. County or Parish, State				
18-31N-16W 360/N= 85	San Juan, NM				
OUTOK ADDDODDIATE DOV	s) TO INDICATE NATURE OF NOTICE, REPO				
TYPE OF SUBMISSION	s) TO INDICATE NATURE OF NOTICE, REFO				
		Change of Flans			
Notice of Intent	Abandonment	New Construction			
	Recompletion	Non-Routine Fracturing			
Subsequent Report	Plugging Back	Water Shut-Off			
—	Casing Repair	Conversion to Injection			
Final Abandonment Notice	Altering Casing	Dispose Water			
	Other	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
See arrach	ed plugging procedure.				

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

API NUMBER	30-045-10840 200 400 1	1 711 1:	25				
OPERATOR NAME	BK PETROLEUM INC	WELL NU	MBER	16			
PROPERTY NAME	MANY ROCKS GALLUP UNIT		1				
SECTION 18	TOWNSHIP 31N	RANGE	16W				
FOOTAGE	360 FNL- 855 FEL UL 'A'						
	Sur Csg OD 12 1/4" HOLE	8 5/8	XX			· · ·	XX
	SUR CSG TD	98	XX	-			XX
	SUR CSG WT	26.4	XX				XX
	TOP OF CMT	0	XX	-			XX
	ACTUAL	CIRC	XX	XX		XX	XX
	CACULATED	85SX	XX	XX	,	XX	XX
	PROD CSG OD 6 3/4 HOLE	4 1/2	XX	XX		XX	XX
	PROD CSG TD	1729	XX	XX		XX	XX
	PROD CSG WT	9.5	XX	XX		XX	XX
	TOP OF CMT	371	XX	XX		XX	XX
FORMATION TOP	ACTUAL		•	ХX		ΧX	'
GALLUP 1493	CACULATED	125SX		XX		XX	
7303	PERF TOP	1528-32	2	XX		XX	
	PERF BOTTOM	1653-58	8	XX		XX	
	PACKER			XX	∇	XX	
	TYPE OF PLUG			XX	\wedge	XX	
	CIBP & CMT			XX		XX	
	CMT			XX		XX	
				XX		XX	

PROPOSED PLUGGING OPERATION

MIRU PU, BOPE, TOOH W/ TUBING & RODS, RIH W/WORK STRING, CIRC HOLE SPOT 14 SX PLUG 1540-1360, WOC TAG, TOP AS REQUIRED, POOH RIH, PERF @ 148', CIRC CMT TO SURFACE, LEAVE CSG FULL, EST 35 SX CUT OFF WELLHEAD, INSTALL P&A MARKER, DIG AND CUT ANCHORS, Close pits according to guidelines: Clean and level location

