Form 9-331 a (Fet 1951)

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Approve	al expire	s 12-31	-U4.			
Land Offi	°°0780	Senta Fe *078096					
Lease No	1/2	<b>&gt;0</b> 0	. 9				
Unit							

	. ND D	EDORTS ON	M ELLO	
SUNDRY NOT	ICES AND R	EFORTS OF		
DOTT		- at WATER	SHII I-UFF	
OTICE OF INTENTION TO DRILL		DEPORT OF SHOULD	AG OK WOLL	
		OF NITERI	MG CNSING	
	Off	TO THE PERSON OF REDRIL	LING OK	
	K METET	COURN'T REPORT OF ABAND	ONMEN I	
		LEMENTARY WELL HISTORY		
OTICE OF INTENTION TO PULL OR ALTER CA	ASINGSUPP	LEMENTALE TO		
NOTICE OF INTENTION TO ABANDON WELL		NOTICE OR OTHE	R DATA)	
(NDICATE ABOVE	E BY CHECK MARK NATURE O	F REPORT, NOTITE	. *4	52
(INDICATE III		Cotobel	r L),	, 19
Vell No. 3 is located	890 ft. from   N   S		(W)	ec
. h. 1/4 sec. 9	(Range	(Meridia	n) now herico	
(14 Sec. and Sec. No.)	(Twp.)		(State or Territory)	
aildest	(County or Subdi	vision)	(State of Tourish 1)	tar)
		1 2 1 1 1	be furnished L	
. C.I. darrick floo	or above sea level is			
The elevation of the derrick floo	DETAILS C	F WORK  white, and lengths of propose appreciant proposed work)	d casings; indicate muddi	ing jobs, cement-
(State names of and expected depths to obj	octive sands; show aizes, weiring points, and all other in	the top of the	Cakota is rea	ch <b>ed</b> , stick
(State names of and expected depths to objust and set 7-5/8" casing, to call or mater is encounted hole will be madded and below the Mess Verde probase of Foint Lookout at 2501 approx 10-3/4" eas 1501 approx 10-3/4" eas	octive sands; show sizes, weiging points, and all other in retary tools to hen drill with gred in the Tools drilling continues non-commerciated completed as ing - Circ.late	the top of the set to Dakota. In the top as to Dakota. In the set to Dakota. In the set to Dakota. In the set to Saria.	matica. Is the Dakota is reachould the form plugged back entire Mass Years of the Community	ched, ation to the rde section
(State names of and expected depths to objust and set 7-5/8" casing, to sail or mater is encounted hole will be madded and below the less verde probase of roint lookout as 250° approx 10-3/4" cas 1500° approx 2-1/2" cas 7600° approx 2" 250° cas 1 20° approx 2" 250° cas 1 20° approx 2" 250°	octive sands; show aizes, weiging points, and all other in retary tools to head drill with a red in the Toeit drilling continued in the Toeit drilling continued completed as ing - Circulate and complete and com	the top of the set to Dakota. In the top as to Dakota. In the set to Dakota. In the set to Dakota. In the set to Saria.	matica. Is the Dakota is reachould the form plugged back entire Mass Years of the Community	ched, ation to the rde section
(State names of and expected depths to objust and set 7-5/8" casing, to sail or mater is encounted hole will be madded and below the less verde probase of roint lookout as 250° approx 10-3/4" cas 1500° approx 2-1/2" cas 7600° approx 2" 250° cas 1 20° approx 2" 250° cas 1 20° approx 2" 250°	octive sands; show aizes, weiging points, and all other in retary tools to head drill with a red in the Toeit drilling continued in the Toeit drilling continued completed as ing - Circulate and complete and com	the top of the set to Dekota for before the ide to Dekota for before the ide to Dekota. In the cessent to surface to sacks of resulting by the Geological Surface by the Geolo	mation. In the Dakota is rea hould the form plugged back entire hass vece lar casent consent.	tion to the rde cection
(State names of and expected depths to objust and set 7-5/8" casing, to sail or mater is encounted hole will be madded and below the less verde probase of roint lookout as 250° approx 10-3/4" cas 1500° approx 2-1/2" cas 7600° approx 2" 250° cas 1 20° approx 2" 250° cas 1 20° approx 2" 250°	octive sands; show aizes, weiging points, and all other in retary tools to head drill with a red in the Toeit drilling continued in the Toeit drilling continued completed as ing - Circulate and complete and com	the top of the set to Dekota for before the ide to Dekota for before the ide to Dekota. In the cessent to surface to sacks of resulting by the Geological Surface by the Geolo	mation. In the Dakota is rea hould the form plugged back entire hass vece lar casent consent.	tion to the rde cection
(State names of and expected depths to obj  Re propose to drill with  and set 7-5/8" casing, to  call or mater is encounted  hole will be madded and  below the less verde pro-  base of roint lookout an  Casing Program:  250' approx 10-1/4" cas  1500' approx. 7-5/8" 26  7600' approx. 5-1/2" cas  1 understand that this plan of work  Company  Address  Address	octive sands; show aizes, weiging points, and all other in retary tools to heat drill with a red in the Toeit drilling continues non-conserving completed as ing - Circulate aims (17) - 100 must receive approval in written of the complete	the top of the set to Dekota for before the ide to Dekota for before the ide to Dekota. In the cessent to surface to sacks of resulting by the Geological Surface by the Geolo	mation. In the Dakota is rea hould the form plugged back entire hass vece lar casent consent.	tion to the rde cection
(State names of and expected depths to obj  Re propose to drill with  and set 7-5/8" casing, to  call or mater is encounted  hole will be madded and  below the less verde pro-  base of roint lookout an  Casing Program:  250' approx 10-1/4" cas  1500' approx. 7-5/8" 26  7600' approx. 5-1/2" cas  1 understand that this plan of work  Company  Address  Address	octive sands; show aizes, weiging points, and all other in retary tools to heat drill with a red in the Toeit drilling continues non-conserving completed as ing - Circulate aims (17) - 100 must receive approval in written of the complete	the top of the set to Dekota for before the ide to Dekota for before the ide to Dekota. In the cessent to surface to sacks of resulting by the Geological Surface by the Geolo	mation. In the Dakota is rea hould the form plugged back entire hass vece lar casent consent.	tion to the rde cection
(State names of and expected depths to objust and set 7-5/8" casing, to sail or mater is encounted hole will be madded and below the less verde probase of roint lookout as 250° approx 10-3/4" cas 1500° approx 2-1/2" cas 7600° approx 2" 250° cas 1 20° approx 2" 250° cas 1 20° approx 2" 250°	octive sands; show aizes, weiging points, and all other in retary tools to heat drill with a red in the Toeit drilling continues non-conserving completed as ing - Circulate aims (17) - 100 must receive approval in written of the complete	the top of the set to Dekota for before the ide to Dekota for before the ide to Dekota. In the cessent to surface to sacks of resulting by the Geological Surface by the Geolo	matica. Is the Dakota is reachould the form plugged back entire Mass Years of the Community	tion to the rde cection

ease	mr. 24		Well No	
ec. 9	т31 N.	, R 11 W.	, N.M.P.M.	
		uth line and	790! from	
the	West line.			
an Juan Co	unty	New M	exico	<b>-</b>
				•
	9			
				7
	<del>  </del>	-		-
190'				N
390				
cale—4 inches	equals 1 mile.			
		plat was prepare		
		under my superve e best of my kno		
			7	1
	-an	west.	milles	<u>C</u>
eal:		Registered Pro		Charles J. Finklea
		Engineer and La	nd Surveyor.	N. Mex. Reg. No. 13