

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

97 JUL 17 PM 1:27

1. Type of Well
GAS

2. Name of Operator

BURLINGTON OIL & GAS COMPANY
OIL CON. DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1068' FSL, 968' FWL, Sec. 12, T-31-N, R-10-W, NMPM
m

5. Lease Number

SF-078389A

6. Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 32-9 Unit

8. Well Name & Number

San Juan 32-9 U #45

9. API Well No.

30-045-10863

10. Field and Pool

Blanco Mesaverde

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Bradenhead repair

13. Describe Proposed or Completed Operations

6-30-97 MIRU. ND WH. NU BOP. TOO H w/162 jts 2 3/8" tbgs. TIH w/5 1/2" csg scraper to 5480'. TOO H. SDON.

7-1-97 TIH w/RBP, set @ 4880'. TOO H. TIH, dump 15 gal sd on top of RBP. TOO H. Load csg w/92 bbl 2% Kcl. PT csg to 1000 psi, OK. Ran CBL @ 3000-4850', TOC on 5 1/2" csg @ 4600'. (Verbal approval to back off 5 1/2" csg @ approximately 3225' from Wayne Townsend, BLM). Blow well & CO. SDON.

7-2-97 Blow well & CO. Load intermediate csg w/60 bbl wtr. TIH w/free point. Chemical cut csg @ 3203'. TOO H w/99 jts 5 1/2" csg. SDON.

7-3-97 TIH w/swedge to top of lnr @ 3203'. Work swedge on lnr top. TOO H w/swedge. TIH w/RBP, set @ 3100'. TOO H. Load 7 5/8" csg w/wtr. PT 7 5/8" csg to 1000 psi, OK. Spot 10 gal sd on top of RBP. Ran CBL @ 0-2250', TOC @ 2004'. SD for weekend. (Verbal approval from Johnny Robinson, OCD to perf sqz holes @ 658'. Left message on BLM answering machine).

7-7-97 TIH, perf 2 sqz holes @ 658'. Pump 10 bbl wtr ahead. Pump 325 sx Class "G" neat cmt w/2% calcium chloride behind 7 5/8" csg @ 0-658'. Circ 1 bbl cmt to surface. Closed bradenhead, sqz 5 bbl away. WOC. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

ACCEPTED FOR RECORD

Signed *[Signature]* Title Regulatory Administrator Date 7/16/97

JUL 31 1997

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date FARMINGTON DISTRICT OFFICE

CONDITION OF APPROVAL, if any:

NMOCD

7-8-97 TIH, tag TOC @ 539'. Drill cmt @ 539-660'. Circ hole clean. PT csg to 1000 psi/20 min, OK. TOOH. TIH w/retrieving tool. Latch RBP, TOOH. RBP stuck @ 650'. TOOH retrieving tool. TIH w/mill. TOOH. SDON.

7-9-97 TIH w/csg scraper to 660'. TOOH. TIH, latch RBP, TOOH. TIH. SDON.

7-10-97 Blow well & CO. TOOH. TIH w/175 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 5485'. ND BOP. NU WH. RD. Rig released.