

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
FEB 19 1997 PM 3:09

1. Type of Well
GAS

RECEIVED
FEB 24 1997

070 FARMINGTON, NM

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL COIL DIV.
DIST. 3
OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1650' FNL, 990' FEL, Sec. 12, T-31-N, R-10-W, NMPM

H

5. Lease Number

SF-078389A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 32-9 Unit

8. Well Name & Number

San Juan 32-9 U #4

9. API Well No.

30-045-10930

10. Field and Pool

Blanco Pictured Cliffs/

~~Blanco Mesaverde 2/~~

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

2-6-97 MIRU. ND WH. NU BOP. TOO H w/110 jts 2 3/8" tbgs. SDON.

2-7-97 TIH w/7" gauge ring to 3370'. TOO H. TIH w/7" CIBP, set @ 3350'. TOO H. TIH, load hole & circ hole clean w/82 bbl wtr. Attempt to PT csg, failed. Plug #1: pump 84 sx Class "B" neat cmt @ 2902-3350'. TOO H to 1868'. Perf 3 sqz holes @ 1954'. TOO H. TIH w/7" cmt retainer, set @ 1868'. PT csg to 750 psi/5 min, OK. SD for weekend.

2-10-97 PT tbgs to 1000 psi, OK. Establish injection. Plug #2: pump 67 sx Class "B" neat cmt outside 7" csg @ 1755-1954' below cmt retainer. Pump 31 sx Class "B" neat cmt inside csg, TOC @ 1703'. TOO H. TIH, perf 3 sqz holes @ 615'. TOO H. Attempt to establish circ out bradenhead w/80 bbl wtr. (Verbal approval to change plans from J. Morris, BLM). Plug #3: pump 26 sx Class "B" neat cmt outside csg @ 515-615'. Pump 37 sx Class "B" neat cmt inside csg, TOC @ 417'. Sqz to 450 psi. WOC. TIH, tag TOC @ 460'. TOO H. TIH, perf 3 sqz holes @ 225'. TOO H. Establish circ down csg & out bradenhead w/14 bbl wtr. Plug #4: pump 101 sx Class "B" neat cmt down 7" csg & out bradenhead. Circ 1 bbl cmt to surface. SDON.

2-11-97 ND BOP. Cut off WH. Fill 7" csg & 7" x 9 5/8" annulus w/10 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 2-11-97. (J. Morris, BLM on location).

14. I hereby certify that the foregoing is true and correct.

Signed *Duane W. Spencer* Title Regulatory Administrator Date 2/17/97

(This space for Federal or State Office use)

APPROVED BY */s/ Duane W. Spencer*

Title

Date FEB 21 1997

CONDITION OF APPROVAL, if any: