

~~RETEST~~

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Undes. Dakota Formation Dakota County San Juan
Initial XX Annual _____ Special _____ Date of Test 9-27-60
Company Delhi-Taylor Oil Corporation Lease Delhi-Wadde Well No. 1
Unit NE/4 Sec. 10 Twp. 31-S Rge. 11-W Purchaser _____
Casing 5-1/2" Wt. 17# I.D. 4.092 Set at 7580 Perf. 7445-55 To 7078-84 7100-05
Tubing 2-3/8 Wt. 4.7# I.D. 1.995 Set at 7154 Perf. Open ended To 7078-84
Gas Pay: From 7078 To 7455 L _____ xG 0.642 -GL _____ Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single gas
Date of Completion: 8-11-60 Packer None Reservoir Temp. _____
Single-Bradenhead-G. G. or G.O. Dual

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter)

Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						<u>2258</u>		<u>2248</u>		<u>7 Days</u>
1.		<u>3/4"</u>	<u>298</u>	<u>85"</u>		<u>298</u>	<u>85"</u>	<u>298</u>		<u>3 Hours</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.385</u>		<u>310</u>	<u>0.9788</u>	<u>0.9809</u>	<u>1.025</u>	<u>3694</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
P_c _____ (1-e^{-s})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2270 P_c 5152900

No.	$\frac{P_w}{P_t}$ (psia)	P_t^2	F _c Q	(F _c Q) ²	$\frac{(F_c Q)^2}{(1-e^{-s})}$	P _w ²	P _c ² -P _w ²	Cal. P _w	$\frac{P_w}{P_c}$
1.									
2.									
3.									
4.									
5.									

Absolute Potential: 4199 MCFPD; n 0.75
COMPANY Delhi-Taylor Oil Corporation
ADDRESS P. O. Drawer 1188
AGENT and TITLE J. F. Berry - Dist. Engineer
WITNESSED Bob Wickell
COMPANY El Paso Natural Gas Company

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .

STATE OF NEW MEXICO	
OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
NUMBER OF COPIES RECEIVED	
DATE OF RECEIPT	
FILE	
INDEX	
LIBRARY	
TRANSPORTER	
PRODUCTION OFFICE	
OPERATOR	