Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

representations as to any matter within its jurisdiction

UNITED STATES DEPARTMENT OF THE INTERIOR

Budget Bureau No. 1004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS SF - 078040 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation 1. Type of Well Oil Well 8. Well Name and No. X Ges Other 16 Mudge LS # 2. Name of Operator Attention: 9. API Well No. Nancy I. Whitaker Amoco Production Company 3004510940 3. Address and Telephone No. (303) 830-5039 10. Field and Pool, or Exploratory Area P.O. Box 800, Denver, Colorado 80201 Eruitland 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11, County or Parish, State Sec. 10 T 31N R 11W UNIT B 920 FNL 1650FEL San Juan New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent New Construction Non-Routine Fracturing Water Shut-Off Subsequent Report Casing Repair Altering Casing Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give 13. Describe Proposed or Completed Operations (Clearly subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) MIRUSU 11-20-96 TOH W/TBG AND PKR. Set CIBP @ 7380'. Loaded and tested csg to 500psi, held okay. spotted cement plug inside csg on top of CIBP from 7110' to 7380', with 41 sxs, 9 bbls of class B neat. Spotted cement plug inside csg from 6200' to 6400' with 22 sxs. 5 bbls of class B neat. Spotted cement plug inside csg. from 4175' to 4400', with 22 sxs, 5 bbls, class B neat. Spotted cement plug inside csg. from 3660' to 3860', with 22 sxs 5 bbls, class B neat. Spotted cement plg inside csg. from 2150' to 2650', with 55 sxs, 12 bbls, class B neat. Spotted cement plug inside csg. from 960' to 1170', with 22 sxs, 5 bbls of class B neat. Shot sqz. holes at 250', could not pump into. shot sqz holes at 180' could not pump into. Shot sqz boles at 60', circ w/water and prepared to pump cement. TIH WITH TBG. TO 270'. Spotted a cement plug inside csg, with 55-sxs, 12 bbls of Class B neat. Circulated 6 bbls of this cement through sqz perfs at 60' to surface out of 7" casing. Cut of WH, Top of surface csg and 7" csg and 5.5" csg with 1 bbls of Class B cement. Install Market RDSUMO 11/26/96 12-16-1996 STAFF ASSISTANT

FORM APPROVED

NMOCO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United