

N M O C C

(SUBMIT IN TRIPLICATE)

Indian Agency _____

UNITED STATES

Navajo Tribal

DEPARTMENT OF THE INTERIOR

Allottee _____

GEOLOGICAL SURVEY

Lease No. 14-20-402-995

	X		

Verbal Approval received 9/21/57, McGrath to Bomer to plug and abandon well.
SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____	SEP 24 1957
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____	FARMINGTON, NEW MEXICO
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____	
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____	
NOTICE OF INTENTION TO ABANDON WELL _____		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo Tribal "B"

Farmington, New Mexico September 23, 1957

Well No. 1 is located 1690 ft. from N line and 1690 ft. from E line of sec. 10

NW 1/4 of Section 10
(1/4 Sec. and Sec. No.)

T-31-N
(Twp.)

R-19-W
(Range)

N.M.P.M.
(Meridian)

Wildcat

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 4961 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging, cementing points, and all other important proposed work)

We propose to plug and abandon the above well as follows:

1. Squeeze present perforations 6400-6410 with 75 sacks of cement.
2. Cut off 5 1/2" pipe at free point (top of cement at 5235 by temperature survey) and spot 40 sack plug across top of stub (10-50 feet into pipe and 50 feet up hole.)
3. Spot 60 sack plug in bottom of 9-5/8" pipe (10-50 feet into hole and 50' up pipe).
4. Cut off 9-5/8" pipe at free point (top of cement at 3510 by temperature survey) and spot 90 sack plug across top of stub (10-50 feet into pipe and 50' up hole.)
5. Spot 300 sack plug 1700'-2000' to isolate fresh water zone.
6. Spot 200 sack plug 900'-1100' to separate Dakota and Harrison.
7. Spot 120 sack plug in bottom of surface (10-50 feet into hole and 50 ft. up pipe) 13-3/8" casing at 534'.
8. Spot 10 sack plug in top of surface casing and correct marker and restore ground to its original contour.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

ORIGINAL SIGNED BY

By D. J. SCOTT

Title Field Clerk