

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Federal <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator El Paso Natural Gas Company	8. Farm or Lease Name Neil
3. Address of Operator Box 990, Farmington, New Mexico	9. Well No. 9 (OWWO)
4. Location of Well UNIT LETTER N 990 FEET FROM THE South LINE AND 1600 FEET FROM THE West LINE, SECTION 4 TOWNSHIP 31N RANGE 11W NMPM.	10. Field and Pool, or Wildcat Blanco Mesa Verde
15. Elevation (Show whether DF, RT, GR, etc.) 6217' GL	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER Case, Cement and Fracture <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

In order to increase deliverability it is intended to workover and restimulate this well in the following manner:

Pull tubing, set a drillable bridge plug near the bottom of the 7" casing and pressure test to 1000 psi. Isolate and squeeze any leaks. If leaks occur and are squeezed between 1090' and 2000' no additional block squeeze of the 7" annulus is planned. If there are no leaks, perforate at approximately 1170' and block squeeze the 7" annulus with a minimum of 100 sacks of cement. Clean out and drill to approximately 5450'. Run a full string of 4 1/2" production casing and sufficient cement to cover the 7" casing shoe. Selectively perforate and fracture the Mesa Verde formation. In the event the tubing is stuck and has to be cut off or other junk in the open hole makes a clean out uneconomical, a drillable cement retainer will be set near the bottom of the 7" casing and the open hole squeezed with approximately 250 sacks of cement. A new side-track hole will be drilled to approximately 5450', all other operations will be as outlined above.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by Carl E. Matthews	TITLE Petroleum Engineer	DATE 11-7-66
SIGNED		
APPROVED BY Emory E. Cawley	TITLE Supt Dist III	DATE 11-8-66
CONDITIONS OF APPROVAL, IF ANY:		



