(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Nev	Mexico	
Lease No	07764	8	
		T-31-N.	,∏-12-W.
		W.M.P.M	•

NOTICE OF	INTENTION TO DRILL		X	_		
i .	INTENTION TO CHANGE PL		SUBSEQUENT	REPORT OF WATER SHUT		
	INTENTION TO TEST WATER		1 10 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	REPORT OF SHOOTING OF		
	INTENTION TO RE-DRILL C			REPORT OF ALTERING CA		
	INTENTION TO SHOOT OR			REPORT OF REDRILLING		
	INTENTION TO PULL OR AL			REPORT OF ABANDONMEN		
	INTENTION TO ABANDON W			ARY WELL HISTORY		
			-			
	(INDICATE	ABOVE BY CHECK MAR	K NATURE OF REPORT	, NOTICE, OR OTHER DATA)		
				Way 2.	·	19 5
SEI, Se	5 Davis is loca	T-31-N.,	R-12-W.	N.M.P.M.	$\left\{\begin{array}{c} E \\ W \end{array}\right\}$ line of sec.	3
Le Fla	ec, and Sec. No.)	^(Twp.) San Jua	(Range)	(Meridian)	exi co	
,=	(Field)	********	y or Subdivision)		e or Territory)	
				Mar San Aramata		
	ion of the derrick f	DETA	ILS OF WORI	(cemeni
ell to expected t this 300'. ubing s	tion of the derrick for and expected depths to one be drilled with at about 5050's point and the second of the used. It is a second about 51	DETA bjective sands; show sing points, and all rotary tool 5-1/2" ca well complete arrace pape of	ILS OF WORI	ths of proposed casings; in osed work) Point Lookout 5 set and cement tools to a tot	Sand, which is depth of the factor of the fa	s seck abou
ell to expected t this 300'. ubing t	be drilled with at about 5050° point and the violation of the point and the violation of the from about 51 dthat this plan of work mand that this plan of work mand the work mand that the work mand the work	DETA bjective sands; show sing points, and all rotary tool 5-1/2" cal complete rface pape cal control will be control to 5300". streceive approval in S COMPANY	ILS OF WORI zes, weights, and leng other important prop s to top of sing will be d with cable emented to s shot with ap writing by the Geolo	ths of proposed casings; in osed work) Point Lockout S set and coment tools to a toturface and about proximately 800	dicate mudding jobs, Send, which is sed with 200 ial depth of it 5250' of 2 duarts of n	s sack abou itro
ell to apected this 300'. ubing ubing understand	be drilled with at about 5050 point and the wind the world of the point and the wind the world of the from about 51 that this plan of work mand the work mand that the work mand that the world work mand that the world work mand that the world work mand the world work man	DETA bjective sands; show sing points, and all rotary tool 5-1/2" cal complete rface pape cal control will be control to 5300". streceive approval in S COMPANY	ILS OF WORI zes, weights, and leng other important prop s to top of sing will be d with cable emented to s shot with ap writing by the Geolo	the of proposed casings; in osed work) Point Lockout Set and coment tools to a tot urface and about proximately 800 proximate	dicate mudding jobs, Sand, which is ted with 200 isal depth of it 5250' of 20 quarts of it follows may be commended.	s sack abou itro

ase	Davis		*******	We	ell No. 5	
ç. <i>3</i> ,	3 T.	3/	N.	12.	W., N.M.	.P.M.
200 i We Being i n Juan Com	n the .	90' N NW 1 S	orth fi E} SE}	com SE sectio	Cor. Son 3.	
		st		1.00		
	s	3.				_
				6	990'	7
			*	990'		

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Seal:

Registered Professional Engineer and Land Surveyor.

Farmington, New Mexico

Surveyed stober 29 49, 19