

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office Santa Fe
Lease No. 87 075215
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF WORKOVER


(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 1 is located 1000 ft. from N line and 1000 ft. from W line of sec. 1
10 (1/4 Sec. and Sec. No.) 10 North 10 West (Twp.) 10 (Range) 10 (Meridian)
10 (Field) 10 (County or Subdivision) 10 (State of Texas)

The elevation of the derrick floor above sea level is 5000 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate casing points, and all other important proposed work)



Moved in Gardner Bros. rotary rig on 5-31-59; pulled tubing, cleaned out to T.D.; ran 853' of 5" 15# J-55 CFI liner w/whirl-down float shoe and float collar spaced 33' apart; set with Beach-Ross hanger, landed at 4259'; cemented with 225 sac (113 regular, 112 pozmix) 2% gel, 12# Gilsomite per sack; put 3 sac gel with 20 bbls water ahead. Squeezed hole in 7" casing with 100 sac regular, 2% calcium chloride; pressured to 2500#.

Perforated Point Lookout at 4914-21, 4931-85, 5023-38, 5053-58, 5066-73, with 2 Lane-Wells jets per foot, 176 total shots; set bridge plug at 4830'.

Perforated Menefee and Cliff House at 4430-48, 4489-4516, 4538-43, 4557-62, 4622-28, 4709-25, 4784-4810, with 2 Lane-Wells Jets per foot, 206 total shots.

Fraced Point Lookout with 50,000 gals. water, 50,000# 20-40 sand, using 4 Dowell Allison's, unable to load hole; put 82 barrels water, and started sand; broke at 1700# to 1150# minimum; average injection rate 68.1 BPM; used 50 balls after 1/3 sand, 50 balls and 25 balls; fair buildup after each drop.

Fraced Cliff House and Menefee with 40,000 gals. water, 40,000# 20-40 sand; breakdown 1800 psi to 1400 minimum; average injection rate 64 BPM; dropped 85 balls.

Ran 102 jts. 2 3/8" tubing, 2 bottom jts. slotted and orange-peeled; total tubing 505.00'; top perforations 4982 KB.

Rig released at 3:00 P.M. 6-14-59.