


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo Tribal

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee \_\_\_\_\_

Lease No. \_\_\_\_\_  
Contract 14-20-600-3530



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON <u>Temp. Juana Lopez</u>	
<u>and Perf. and Frac. G. Horvath</u>	

RECEIVED  
JUN 19 1963

U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 18, 1963

Quinsey Rock  
Well No. 14-6 is located 330 ft. from S line and 330 ft. from W line of sec. 6

S 1/4 Sec. 6 31N 16E NMPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Unamed San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the KB surface above sea level is 5320 ft. Ord. 5308.5

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to Temp. Aband. the Juana Lopez and develop the upper horizons as follows:

1. Set a Baker 5 1/2" magnesium drillable Bridge Plug at 1290. Press. set to 3500 PSI for 30 Min.
2. Perf. and Frac. sand at 1160/1188.
3. Put well on production.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Soccony Mobil Oil Co., Inc.

Address P. O. Box 3371

Durango, Colorado

By M. J. Meyer

Title Dr. Prod. Foreman