

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078509

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 32-9 Unit

8. FARM OR LEASE NAME

San Juan 32-9 Unit

9. WELL NO.

32

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T-32-N, R-9-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

990'S, 990'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6775' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒
☐
☐

Final Notice

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well was plugged and abandoned between 10-6 and 10-12-76 in the following manner:

1. Spot a 25 sack cement plug across the top of the Pictured Cliffs formation (3495-3628).
2. Perforated squeeze holes at 3000', spot 60 sack cement plug pressure displace 20 sacks through perforations.
3. Perforated squeeze holes at 1500', spot 60 sack cement plug pressure displace 20 sacks through perforations.
4. Perforated squeeze holes at 310', spot 60 sack cement plug pressure displace 20 sacks through perforations.
5. Placed a 10 sack plug at the surface, installed dry hole marker.

Note: This well is located on the same location as the San Juan 32-9 #32R. The location will not be restored until the above mentioned well has been plugged.

NOV 8 1976

18. I hereby certify that the foregoing is true and correct

SIGNED

A. P. Davis

TITLE

Drilling Clerk

DATE

October 29, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

NOV 2 1976

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.