

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED

5. Lease Number

SF-07807

6. If Indian, All or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Scott #5

9. API Well No.

30-045-11172

10. Field and Pool

Blanco Mesa Verde

11. County and State

San Juan County, NM

1. Type of Well
GAS

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec, T, R, M.
1649'N, 799'E Sec. 34, T-27-N, R-10-W, NMPM
32

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut Off

☐ Conversion to Injection

RECEIVED

MAY 24 1990

13. Describe Proposed or Completed Operations

OIL CON. DIV.

DIST. 3

04-19-90 MOL&RU.
04-20-90 Cleaned cmt out of pipe rams. Blew well down. Kill well w/1% KCl. NDWH. NU BOP. TOO H w/tbg. TIH w/tbg, scraper & bit to 4676'. TOO H. SD for weekend
04-21-90 TIH, set RBP @ 4614'. Load hole & PT to 1500#/15 min, ok. TIH, logged GR-CCL & CBL 4614-900'. Log failed @ 880'. TOO H. TOC 4200'. Ratty to 3500'. Perf 2 holes @ 3436'. Pumped into formation. TIH w/tbg & fullbore pkr set @ 3236'. Squeezed perfs w/100 sx 65/35 Class "B" Poz w/6% gel, 2% calcium chloride and 1/2 cf perlite/sx. Tail w/50 sx Class "B" w/2% calcium chloride. Circ tbg. clean. SDFN.
04-24-90 Released pkr. TOO H. TIH w/tbg, bit & scraper. Tag cmt @ 3269'. Drld squeeze & circ hole clean. PT csg 1500#/15 min. Ran GR, CCL-CBL 3850-3200', 900-50'. Squeeze cmt 3700-3372'. TIH, shot 2 holes @ 3285'. Pump 100 sx 65/35 Poz Class "B" w/6% gel, 2% calcium chloride and 1/2 cu.ft. perlite/sx. Reversed tbg clean. Repressured to 1500#. SDFN. (cont'd on back)

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Regulatory Affairs Date 5-3-90

ACCEPTED FOR RECORD

(This space for Federal or State office use)

MAY 18 1990

APPROVED BY
CONDITION OF APPROVAL, IF ANY:

TITLE

NMOCD

DATE
FARMINGTON RESOURCE AREA
BY Ken Townsend

Scott #5

- 04-25-90 Release pkr. TOOH. TIH, tag cmt @ 3172'. Drld squeeze. Circ hole clean. PT csg 1000#/15 min. Ran GR-CCL, CBL 3350-3000'. Squeeze covered 101'. Perf csg @ 2950'. Squeeze perf w/100 sx Class "B" 65/35 Poz w/6% gel, 6.25# gilsonite, 2% calcium chloride, followed w/50 sx Class "B" w/2% calcium chloride tail. SDFN.
- 04-26-90 Released pkr. TOOH. Blew well down. TIH, tag cmt @ 2863'. Drld squeeze. Circ hole clean. PT csg 1150#/15 min. TOOH. Ran GR-CCL & CBL 3200-2550'. TOC @ 2660'. Perf 2 squeeze holes @ 2585'. TIH w/7" fullbore pkr set @ 2385'. Squeezed perf w/100 sx Class "B" 65/35 Poz w/6% gel, 2% calcium chloride & 6.25# gilsonite/sx, tailed w/100 sx Class "B" w/2% calcium chloride. Pressured squeeze. Rerversed tbg clean. SDFN.
- 04-27-90 Released pkr. TOOH w/tbg & pkr. TIH. Tag cmt @ 2500'. Drld squeeze & circ clean. PT 1150#/15 min, ok. TOOH. Ran GR-CCL & CBL 2800-1400'. TCO @ 1775'. Perf 2 holes @ 1310'. Squeeze cmt'd w/100 sx 65/35 Poz w/6% gel, 2% calcium chloride and 6.25#/sx gilsonite, followed by 200 sx Class "B" w/2% calcium chloride. Recovered 70 bbls wtr. Did not circ to surface. Left 10 sx in csg. Circ pkr & tbg clean. SDFN.
- 04-28-90 TOOH. TIH, tag cmt @ 127'. Drld squeeze, circ hole clean. PT csg 1100/15 min, ok. TOOH. Ran GR, CCL & CBL 1500' to TC @ 530'. Perf 2 holes @ 460'. TIH, set pkr @ 400'. Squeezed w/161 sx Class "B" neat, circ to surface. Squeezed csg to 600# w/cmt left @ perf in csg. Circ tbg clean. SD for weekend.
- 04-30-90 TOOH w/tbg & pkr. TIH, tag cmt @ 435'. Drld squeeze. Circ hole clean. TIH to 2000'. PT csg 1100#/15 min. TIH, tag fill on BP @ 4466'. Circ clean. TIH, blow well dry. TIH to top of RBP, blow out. Retrieved RBP. TOOH w/tbg & RBP. SDFN.
- 05-01-90 TIH, clean out to 5243'. Landed 158 jts 2 3/8", J-55 EUE tbg @ 4922'. SN @ 4800'. ND BOP. NU WH. Released rig.