

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1650' FNL, 990' FEL, Sec. 29, T-32-N, R-10-W, NMPM

5. Lease Number
SF-078604

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Scott #1

9. API Well No.
30-045-11262

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

1-24-96 MIRU. ND WH. NU BOP. Tbg stuck. TIH w/1 13/16" gauge ring to 4520'. TIH w/1 13/16" chemical cutter. Cut tbg off @ 4506'. TOOH w/2 3/8" tbg. SDON.

1-25-96 TIH w/7" gauge ring to 4506'. TOOH. TIH w/BP, set @ 4467'. TOOH. TIH to 4467'. Load hole w/137 bbl wtr, circ hole clean. PT csg to 500 psi, failed. Plug #1: pump 20 sx Class "B" cmt inside csg @ 4363-4467'. TOOH to 2979'. Perf 3 sqz holes @ 3038'. TOOH. TIH w/7" cmt retainer, set @ 2979'. PT tbg to 1500 psi, OK. Load hole w/24 bbl wtr. PT csg to 500 psi, failed. Attempt to establish injection, failed. (Verbal approval to change plans from Joe Ruybalid, BLM). Plug #2: pump 20 sx Class "B" cmt inside csg @ 2875-2979'. TOOH to 2575'. Plug #3: pump 35 sx Class "B" cmt @ 2394-2575'. TOOH to 1936'. WOC. SDON.

1-26-96 TIH, tag TOC @ 2389'. Load csg w/6 bbl wtr. PT csg to 500 psi, failed. TOOH. Perf 3 sqz holes @ 1247'. TOOH. TIH w/cmt retainer, set @ 1179'. Establish injection. Plug #4: pump 81 sx Class "B" cmt below cmt retainer outside 7" csg @ 982-1247', pump 48 sx Class "B" cmt above cmt retainer, TOC @ 930'. TOOH. TIH, perf 3 sqz holes @ 212'. Establish circ down csg & out bradenhead. Plug #5: pump 115 sx Class "B" cmt down 7" csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Fill csg w/48 sx Class "B" cmt. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 1-25-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 2/6/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Date

APPROVED

FEB 16 1996

[Signature]
DISTRICT MANAGER

NMOCD